

MICRO ELECTRONICS

2612G
(AG2612G)

LED BACKLIGHT
FOR LCD DISPLAY


ABSOLUTE MAXIMUM RATINGS

| | | |
|-----------------------|-----------|--------------|
| Forward Current | I_F | 220mA |
| Reverse Voltage | V_R | 10V |
| Operating Temperature | T_{opr} | -20 to +70°C |
| Storage Temperature | T_{stg} | -30 to +80°C |


ELECTRO-OPTICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$)

| PARAMETER | SYMBOL | MIN | TYP | MAX | UNIT | CONDITIONS |
|--------------------------|-----------------|-----|-----|-----|------------------------|--------------------|
| Forward Voltage | V_F | 3.8 | 4.1 | 4.4 | V | $I_F=110\text{mA}$ |
| Reverse Current | I_R | | | 110 | μA | $V_R=10\text{V}$ |
| Peak Wavelength | λ_p | | 565 | | nm | $I_F=110\text{mA}$ |
| Spectral Line Half Width | $\Delta\lambda$ | | 40 | | nm | $I_F=110\text{mA}$ |
| Brightness | B | 50 | | | cd/m^2 | $I_F=110\text{mA}$ |

MECHANICAL OUTLINE



CIRCUIT DIAGRAM



MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex: 43510 Micro Hx. Tel: 2343 0181-5