


IRG4CC81KB



600 V
 Size 8.1
 Ultra-Fast Speed
 Short Circuit Rated
 6" Wafer

Electrical Characteristics (Wafer Form)

Parameter	Description	Guaranteed (Min/Max)	Test Conditions
$V_{CE(on)}$	Collector-to-Emitter Saturation Voltage	4.5V Max.	$I_C = 10A, T_J = 25^\circ C, V_{GE} = 15V$
$V_{(BR)CES}$	Collector-to-Emitter Breakdown Voltage	600V Min.	$T_J = 25^\circ C, I_{CES} = 250\mu A, V_{GE} = 0V$
$V_{GE(th)}$	Gate Threshold Voltage	3.0V Min., 6.5V Max.	$V_{GE} = V_{CE}, T_J = 25^\circ C, I_C = 1.0mA$
I_{CES}	Zero Gate Voltage Collector Current	200 μA Max.	$T_J = 25^\circ C, V_{CE} = 600V$
I_{GES}	Gate-to-Emitter Leakage Current	$\pm 11 \mu A$ Max.	$T_J = 25^\circ C, V_{GE} = +/- 20V$

Mechanical Data

Nominal Backmetal Composition, Thickness:	Cr-NiV-Ag (1k $^\circ$ -2k $^\circ$ -2.5k $^\circ$)
Nominal Front Metal Composition, Thickness:	99% Al, 1% Si (4 microns)
Dimensions:	.523" x .523"
Wafer Diameter:	150mm, with std. < 100 > flat
Wafer thickness:	.015" + / - .003"
Relevant Die Mechanical Dwg. Number	01-5351
Minimum Street Width	100 Microns
Reject Ink Dot Size	0.25mm Diameter Minimum
Ink Dot Location	Consistent throughout same wafer lot
Recommended Storage Environment:	Store in original container, in dessicated nitrogen, with no contamination
Recommended Die Attach Conditions	For optimum electrical results, die attach temperature should not exceed 300C

Reference Standard IR packaged part (for design) : N/A

Die Outline

