


DESCRIPTION

A high efficiency red and green lamp made of GaAlAs, GaP offering a changing color characteristics dependent on the direction the lamp is biased. These two light emitting diodes are mounted in 3mm dual color, white diffused lens.



ABSOLUTE MAXIMUM RATINGS

Power Dissipation @ Ta=25°C
 Forward Current, DC (IF)
 Reverse Voltage
 Operating & Storage Temperature Range
 Lead Soldering Temperature (1/16" from body)

SUPER RED

95mW
 40mA
 5V

GREEN

90mW
 30mA
 5V

-55 to +100°C
 260°C for 5 sec.

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	SUPER RED	GREEN	UNIT	CONDITIONS
Forward Voltage	MAX VF	2.4	3.0	V	IF=20mA
Reverse Breakdown Voltage	MIN BVR	5	5	V	IR=100μA
Luminous Intensity	MIN IV	9	15	mcd	IF=20mA
	TYP	12	20	mcd	IF=20mA
Peak Wavelength	TYP λp	660	568	nm	IF=20mA
Spectral Line Half Width	TYP Δλ	20	30	nm	IF=20mA
Viewing Angle	TYP 2θ 1/2	100	100	degree	IF=20mA










MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex: 43510 Micro Hx. Tel: 2343 0181-5

MSGB39WP(GREEN COLOR)



MSG39WP(RED COLOR)

