

# 1S2076

## Silicon Epitaxial Planar Diode for Various Detector,Modulator,Demodulator

# HITACHI


Rev. 1  
Aug. 1995

**Features**

- Low capacitance. ( $C=3.0\text{pF}$  max)
- Short reverse recovery time. ( $t_{rr}=8.0\text{ns}$  max)
- High reliability with glass seal.

**Ordering Information**

Type No.	Cathode band	Package Code
1S2076	Light Blue	DO-35

**Outline****Absolute Maximum Ratings (Ta = 25°C)**


Item	Symbol	Value	Unit
Peak reverse voltage	$V_{RM}$	35	V
Reverse voltage	$V_R$	30	V
Peak forward current	$I_{FM}$	450	mA
Non-Repetitive peak forward surge current	$I_{FSM}^*$	1	A
Average forward current	$I_o$	150	mA
Power dissipation	$P_d$	250	mW
Junction temperature	$T_j$	175	°C
Storage temperature	$T_{stg}$	-65 to +175	°C

\* Within 1s forward surge current.


**Electrical Characteristics (Ta = 25°C)**

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Forward voltage	$V_F$	0.64	—	0.80	V	$I_F = 10\text{ mA}$
Reverse current	$I_R$	—	—	0.1	$\mu\text{A}$	$V_R = 30\text{ V}$
Capacitance	C	—	—	3.0	pF	$V_R = 1\text{ V}$ , $f = 1\text{ MHz}$
Reverse recovery time	$t_{rr}^*$	—	—	8.0	ns	$I_F=I_R=10\text{mA}$ , $I_{rr}=1\text{mA}$


\* Reverse recovery time test circuit




# 1S2076



**Fig.1** Forward current Vs.  
Forward voltage




**Fig.2** Reverse current Vs.  
Reverse voltage



**Fig.3** Capacitance Vs.  
Reverse voltage

**Package Dimensions**

Unit: mm



---

HITACHI Code	DO-35
JEDEC Code	DO-35
EIAJ Code	SC-48
Weight (g)	0.13

---