



January 2006

FDMA430NZ

Single N-Channel 2.5V Specified PowerTrench® MOSFET

30V, 5.0A, 40mΩ

General Description

This Single N-Channel MOSFET has been designed using Fairchild Semiconductor's advanced Power Trench process to optimize the $R_{DS(on)}$ @ $V_{GS}=2.5V$ on special MicroFET leadframe.



Applications

- Li-Ion Battery Pack



Features

- $R_{DS(on)} = 40m\Omega$ @ $V_{GS} = 4.5 V$, $I_D = 5.0A$
- $R_{DS(on)} = 50m\Omega$ @ $V_{GS} = 2.5 V$, $I_D = 4.5A$
- Low Profile-0.8mm maximum-in the new package MicroFET 2x2 mm
- RoHS Compliant



Absolute Maximum Ratings $T_A = 25^\circ C$ unless otherwise noted

| Symbol | Parameter | Ratings | Units |
|----------------|--|-------------|-------|
| V_{DSS} | Drain-Source Voltage | 30 | V |
| V_{GSS} | Gate-Source Voltage | ± 12 | V |
| I_D | Drain Current -Continuous | 5.0 | A |
| | -Pulsed | 20 | |
| P_D | Power dissipation (Steady State) | (Note 1a) | W |
| | (Note 1b) | 0.9 | |
| T_J, T_{STG} | Operating and Storage Junction Temperature Range | -55 to +150 | °C |
| | | | |

Thermal Characteristics

| | | | | |
|-----------------|---|-----------|-----|------|
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | (Note 1a) | 145 | °C/W |
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | (Note 1b) | 52 | °C/W |

Package Marking and Ordering Information

| Device Marking | Device | Reel Size | Tape Width | Quantity |
|----------------|-----------|-----------|------------|------------|
| 430 | FDMA430NZ | 7" | 12mm | 3000 units |

Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--------|-----------|-----------------|-----|-----|-----|-------|
|--------|-----------|-----------------|-----|-----|-----|-------|

Off Characteristics

| | | | | | | |
|-----------------------------------|---|---|----|------|----------|----------------------------|
| V_{VDSS} | Drain-Source Breakdown Voltage | $V_{GS} = 0\text{V}$, $I_D = 250\mu\text{A}$ | 30 | | | V |
| ΔV_{VDSS} ΔT_J | Breakdown Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$, Referenced to 25°C | | 25.2 | | $\text{mV}/^\circ\text{C}$ |
| I_{DSS} | Zero Gate Voltage Drain Current | $V_{DS} = 24\text{V}$, $V_{GS} = 0\text{V}$, | | | 1 | μA |
| I_{GSS} | Gate-Body Leakage, | $V_{GS} = \pm 12\text{V}$, $V_{DS} = 0\text{V}$ | | | ± 10 | μA |

On Characteristics (Note 2)

| | | | | | | |
|--|--|--|-----|------|-----|----------------------------|
| $V_{GS(\text{th})}$ | Gate Threshold Voltage | $V_{DS} = V_{GS}$, $I_D = 250\mu\text{A}$ | 0.6 | 0.81 | 1.5 | V |
| $\Delta V_{GS(\text{th})}$ ΔT_J | Gate Threshold Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$, Referenced to 25°C | | -3.2 | | $\text{mV}/^\circ\text{C}$ |
| $R_{DS(\text{ON})}$ | Static Drain-Source On-Resistance | $V_{GS} = 4.5\text{V}$, $I_D = 5.0\text{A}$ | | 23.6 | 40 | $\text{m}\Omega$ |
| | | $V_{GS} = 4.0\text{V}$, $I_D = 5.0\text{A}$ | | 23.9 | 41 | |
| | | $V_{GS} = 3.1\text{V}$, $I_D = 4.5\text{A}$ | | 25.4 | 43 | |
| | | $V_{GS} = 2.5\text{V}$, $I_D = 4.5\text{A}$ | | 27.6 | 50 | |
| | | $V_{GS} = 4.5\text{V}$, $I_D = 5.0\text{A}$, $T_J = 150^\circ\text{C}$ | | 37.0 | 61 | |
| g_{FS} | Forward Transconductance | $V_{DS} = 5\text{V}$, $I_D = 5.0\text{A}$ | | 25.6 | | S |

Dynamic Characteristics

| | | | | | | |
|-----------|------------------------------|--|--|-----|-----|----------|
| C_{iss} | Input Capacitance | $V_{DS} = 10\text{V}$, $V_{GS} = 0\text{V}$, $f = 1.0\text{MHz}$ | | 600 | 800 | pF |
| C_{oss} | Output Capacitance | | | 110 | 150 | pF |
| C_{rss} | Reverse Transfer Capacitance | | | 75 | 115 | pF |
| R_G | Gate Resistance | $f = 1.0\text{MHz}$ | | 3.5 | | Ω |

Switching Characteristics (Note 2)

| | | | | | | |
|--------------|---------------------|---|--|------|----|----|
| $t_{d(on)}$ | Turn-On Delay Time | $V_{DD} = 10\text{V}$, $I_D = 1\text{A}$ $V_{GS} = 4.5\text{V}$, $R_{GEN} = 6\Omega$ | | 8.3 | 17 | ns |
| t_r | Turn-On Rise Time | | | 7.1 | 15 | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | | 18.1 | 37 | ns |
| t_f | Turn-Off Fall Time | | | 6.0 | 12 | ns |
| Q_g | Total Gate Charge | $V_{DS} = 10\text{V}$, $I_D = 5.0\text{A}$, $V_{GS} = 4.5\text{V}$ | | 7.3 | 11 | nC |
| Q_{gs} | Gate-Source Charge | | | 0.8 | 2 | nC |
| Q_{gd} | Gate-Drain Charge | | | 1.9 | 3 | nC |

Drain-Source Diode Characteristics and Maximum Ratings

| | | | | | | |
|----------|---|--|--|------|-----|----|
| I_S | Maximum Continuous Drain-Source Diode Forward Current | | | 2.0 | A | |
| V_{SD} | Drain-Source Diode Forward Voltage | $V_{GS} = 0\text{V}$, $I_S = 2.0\text{A}$ | | 0.69 | 1.2 | V |
| t_{rr} | Diode Reverse Recovery Time | $I_F = 5.0\text{A}$, | | | 17 | ns |
| Q_{rr} | Diode Reverse Recovery Charge | $dI/dt = 100\text{A}/\mu\text{s}$ | | | 5 | nC |

Notes:

- R_{WA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.
 - 145°C/W when mounted on a minimum pad of 2 oz copper
 - 52°C/W when mounted on a 1 in² pad of 2 oz copper
- Pulse Test: Pulse Width < 300 μs , Duty Cycle < 2.0%
- The diode connected between the gate and the source serves only as protection against ESD. No gate overvoltage rating is implied.

FDMA430NZ Single N-Channel 2.5V specified PowerTrench® MOSFET

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted




Figure 1. On Region Characteristics




Figure 2. On-Resistance vs Drain Current and Gate Voltage




Figure 3. Normalized On Resistance vs Junction Temperature




Figure 4. On-Resistance vs Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs Source Current

FDMA430NZ Single N-Channel 2.5V specified PowerTrench® MOSFET

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs Drain to Source Voltage




Figure 9. Safe Operating Area




Figure 10. Maximum Continuous Drain Current vs Ambient Temperature




Figure 11. Single Pulse Maximum Power Dissipation

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted





Figure 12. Transient Thermal Response Curve

FDMA430NZ Single N-Channel 2.5V specified PowerTrench® MOSFET

Dimensional Outline and Pad Layout



NOTES:

- A. NOT FULLY CONFORM TO JEDEC REGISTRATION MO-229 DATED AUG/2003.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994

MLP06LrevA

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

| | | | | |
|--------------------------------------|---------------------|---------------|---------------------|-----------------|
| ACEx™ | FAST® | ISOPLANAR™ | PowerSaver™ | SuperSOT™-6 |
| ActiveArray™ | FASTR™ | LittleFET™ | PowerTrench® | SuperSOT™-8 |
| Bottomless™ | FPS™ | MICROCOUPLER™ | QFET® | SyncFET™ |
| Build it Now™ | FRFET™ | MicroFET™ | QS™ | TinyLogic® |
| CoolFET™ | GlobalOptoisolator™ | MicroPak™ | QT Optoelectronics™ | TINYOPTO™ |
| CROSSVOLT™ | GTO™ | MICROWIRE™ | Quiet Series™ | TruTranslation™ |
| DOME™ | HiSeC™ | MSX™ | RapidConfigure™ | UHC™ |
| EcoSPARK™ | I ² C™ | MSXPro™ | RapidConnect™ | UltraFET® |
| E ² CMOS™ | i-Lo™ | OCX™ | μSerDes™ | UniFET™ |
| EnSigna™ | ImpliedDisconnect™ | OCXPro™ | ScalarPump™ | VCX™ |
| FACT™ | IntelliMAX™ | OPTOLOGIC® | SILENT SWITCHER® | Wire™ |
| FACT Quiet Series™ | | OPTOPLANAR™ | SMART START™ | |
| Across the board. Around the world.™ | | PACMAN™ | SPM™ | |
| The Power Franchise® | | POP™ | Stealth™ | |
| Programmable Active Droop™ | | Power247™ | SuperFET™ | |
| | | PowerEdge™ | SuperSOT™-3 | |

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS**Definition of Terms**

| Datasheet Identification | Product Status | Definition |
|--------------------------|------------------------|---|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |

Rev. I17