



**AOT430**

**N-Channel Enhancement Mode Field Effect Transistor**



**General Description**

The AOT430 uses advanced trench technology and design to provide excellent  $R_{DS(ON)}$  with low gate charge. This device is suitable for use in PWM, load switching and general purpose applications. *Standard Product AOT430 is Pb-free (meets ROHS & Sony 259 specifications).*

**Features**

$V_{DS}$  (V) = 75V  
 $I_D$  = 80 A ( $V_{GS}$  = 10V)  
 $R_{DS(ON)}$  < 11.5m $\Omega$  ( $V_{GS}$  = 10V)

**UIS TESTED!**



**Absolute Maximum Ratings  $T_A=25^\circ\text{C}$  unless otherwise noted**

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	75	V
Gate-Source Voltage	$V_{GS}$	$\pm 25$	V
Continuous Drain Current	$I_D$	$T_C=25^\circ\text{C}$ <sup>G</sup>	80
		$T_C=100^\circ\text{C}$	78
Pulsed Drain Current <sup>C</sup>	$I_{DM}$	200	A
Avalanche Current <sup>C</sup>	$I_{AR}$	45	A
Repetitive avalanche energy L=0.3mH <sup>C</sup>	$E_{AR}$	300	mJ
Power Dissipation <sup>B</sup>	$P_D$	$T_C=25^\circ\text{C}$	268
		$T_C=100^\circ\text{C}$	134
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 175	$^\circ\text{C}$

**Thermal Characteristics**

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	45	60	$^\circ\text{C/W}$
Steady-State				
Maximum Junction-to-Case <sup>B</sup>	$R_{\theta JC}$	0.45	0.56	$^\circ\text{C/W}$
Steady-State				

Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}$ , $V_{GS}=0\text{V}$	75			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=60\text{V}$ , $V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$			1 5	$\mu\text{A}$
$I_{GSS}$	Gate-Body leakage current	$V_{DS}=0\text{V}$ , $V_{GS}=\pm 25\text{V}$			1	$\mu\text{A}$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$ , $I_D=250\mu\text{A}$	2	2.7	4	V
$I_{D(ON)}$	On state drain current	$V_{GS}=10\text{V}$ , $V_{DS}=5\text{V}$	200			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}$ , $I_D=30\text{A}$ $T_J=125^\circ\text{C}$		9.8 16.0	11.5 19.0	$\text{m}\Omega$
$g_{FS}$	Transconductance	$V_{DS}=5\text{V}$ , $I_D=80\text{A}$		90		S
$V_{SD}$	Diode Forward Voltage	$I_S=1\text{A}$ , $V_{GS}=0\text{V}$		0.7	1	V
$I_S$	Maximum Body-Diode Continuous Current <sup>G</sup>				80	A
<b>DYNAMIC PARAMETERS</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0\text{V}$ , $V_{DS}=30\text{V}$ , $f=1\text{MHz}$		4700		pF
$C_{oss}$	Output Capacitance			400		pF
$C_{riss}$	Reverse Transfer Capacitance			180		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}$ , $V_{DS}=0\text{V}$ , $f=1\text{MHz}$		3		$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}$ , $V_{DS}=30\text{V}$ , $I_D=30\text{A}$		114		nC
$Q_{gs}$	Gate Source Charge			33		nC
$Q_{gd}$	Gate Drain Charge			18		nC
$t_{D(on)}$	Turn-On DelayTime	$V_{GS}=10\text{V}$ , $V_{DS}=30\text{V}$ , $R_L=1\Omega$ , $R_{GEN}=3\Omega$		21		ns
$t_r$	Turn-On Rise Time			39		ns
$t_{D(off)}$	Turn-Off DelayTime			70		ns
$t_f$	Turn-Off Fall Time			24		ns
$t_{rr}$	Body Diode Reverse Recovery Time		$I_F=30\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$		53	
$Q_{rr}$	Body Diode Reverse Recovery Charge	$I_F=30\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$		143		nC

A: The value of  $R_{\theta JA}$  is measured with the device in a still air environment with  $T_A=25^\circ\text{C}$ .

B: The power dissipation  $P_D$  is based on  $T_{J(MAX)}=175^\circ\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C: Repetitive rating, pulse width limited by junction temperature  $T_{J(MAX)}=175^\circ\text{C}$ .

D: The  $R_{\theta JA}$  is the sum of the thermal impedance from junction to case  $R_{\theta JC}$  and case to ambient.

E: The static characteristics in Figures 1 to 6 are obtained using  $<300\mu\text{s}$  pulses, duty cycle 0.5% max.

F: These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of  $T_{J(MAX)}=175^\circ\text{C}$ .

G: The maximum current rating is limited by bond-wires.

Rev2: Feb 2007

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note F)




Figure 10: Single Pulse Avalanche capability




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 12: Current De-rating (Note B)




Figure 13: Power De-rating (Note B)