


SOT89 NPN SILICON PLANAR MEDIUM POWER TRANSISTOR

ISSUE 3 - NOVEMBER 1995

FCX493

COMPLEMENTARY TYPE – FCX593

PARTMARKING DETAIL – N93



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	120	V
Collector-Emitter Voltage	V_{CEO}	100	V
Emitter-Base Voltage	V_{EBO}	5	V
Continuous Collector Current	I_C	1	A
Peak Pulse Current	I_{CM}	2	A
Base Current	I_B	200	mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	1	W
Operating and Storage Temperature Range	$T_j; T_{stg}$	-65 to +150	°C

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Breakdown Voltages	$V_{(BR)CBO}$	120		V	$I_C=100\mu\text{A}$
	$V_{CEO(\text{sus})}$	100		V	$I_C=10\text{mA}^*$
	$V_{(BR)EBO}$	5		V	$I_E=100\mu\text{A}$
Collector Cut-Off Currents	I_{CBO}		100	nA	$V_{CB}=100\text{V}$
	I_{CES}		100	nA	$V_{CES}=100\text{V}$
Emitter Cut-Off Current	I_{EBO}		100	nA	$V_{EB}=4\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$		0.3	V	$I_C=500\text{mA}, I_B=50\text{mA}$
			0.6	V	$I_C=1\text{A}, I_B=100\text{mA}$
Base-Emitter Saturation Voltage	$V_{BE(\text{sat})}$		1.15	V	$I_C=1\text{A}, I_B=100\text{mA}$
Base-Emitter Turn On Voltage	$V_{BE(\text{on})}$		1.0	V	$I_C=1\text{A}, V_{CE}=10\text{V}$
Static Forward Current Transfer Ratio	h_{FE}	100			$I_C=1\text{mA}, V_{CE}=10\text{V}^*$
		100			$I_C=250\text{mA}, V_{CE}=10\text{V}^*$
		60			$I_C=500\text{mA}, V_{CE}=10\text{V}^*$
		20	300		$I_C=1\text{A}, V_{CE}=10\text{V}^*$
Transition Frequency	f_T	150		MHz	$I_C=50\text{mA}, V_{CE}=10\text{V}$ $f=100\text{MHz}$
Collector-Base Breakdown Voltage	C_{obo}		10	pF	$V_{CB}=10\text{V}, f=1\text{MHz}$

*Measured under pulsed conditions. Pulse width=300μs. Duty cycle ≤ 2%
For typical Characteristics graphs see FMMT493 datasheet.