


KVR133X64C3L/512**512MB 64M x 64-Bit PC133****CL3 Low Profile 168-Pin DIMM****DESCRIPTION:**

This document describes ValueRAM's 64M x 64-bit (512MB) CL3 SDRAM (Synchronous DRAM) 133MHz low profile memory module. The components on this module include sixteen 32M x 8-bit (8M x 8-bit x 4 Bank) PC133 CL3 SDRAM in TSOP packages. This 168-pin DIMM uses gold contact fingers and requires +3.3V. The electrical and mechanical specifications are as follows:

FEATURES:

| | |
|--|--|
| <input checked="" type="checkbox"/> CLK Cycle Time (tCC) | min. = 7.5ns (CAS Latency = 3) / max. = 1000ns |
| <input checked="" type="checkbox"/> Row Cycle Time (tRC) | 65ns |
| <input checked="" type="checkbox"/> CLK to Output (tSAC) | max. = 5.4ns (CAS Latency = 3) |
| <input checked="" type="checkbox"/> Single Power Supply of | +3.3V (+/- .3V) |
| <input checked="" type="checkbox"/> Power | 4.125 W (operating) |
| <input checked="" type="checkbox"/> UL Rating | 94 V - 0 |

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.2" (30.48mm).

**Figure 1: KVR133X64C3L/512 168-Pin SDRAM Module**