


Part Number: NT05 25311

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Not Available

For example: to order an inside kinked lead use part number NT05 25311-A



Electrical Specifications:

Zero-Power Resistance @ 25°C	25.0K $\Omega \pm 10\%$
Resistance @ 0°C/ Resistance @ 50°C	10.45 $\pm 1\%$
Resistance @ 25°C/ Resistance @ 125°C	38.7 $\pm 1\%$
Beta	4250 $\pm 1\%$
Temp Coefficient of Resistance @ 25°C	-4.78%/°C
Operating Temperature Range	-50°C/150°C
Maximum Permissible Power	0.45 W
Dissipation Constant	4.5mW/°C
Thermal Time Constant	10 seconds

Mechanical Specifications:

D	5.0 ± 0.5 mm
T	3.0 mm Max
Lead Diameter	0.5 mm Nom
S	5.0 ± 0.2 mm
L	38.0 mm Min
Straight Leads	Standard

Revision Date: August 12, 2002

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
 Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

www.ametherm.com



DATA SHEET

Part Number: NT05 25311

Resistance Temperature Curve:

Temperature	R@T/R@25°C
-50	86.49
-45	58.59
-40	40.70
-35	30.44
-30	20.73
-25	15.65
-20	11.03
-15	8.513
-10	6.119
-5	4.763
0	3.510
5	2.748
10	2.078
15	1.630
20	1.267
25	1.000
30	0.7942
35	0.6524
40	0.5105
45	0.4243
50	0.3359
55	0.2810
60	0.2259
65	0.1907
70	0.1550
75	0.1317
80	0.1084
85	0.09268
90	0.07708
95	0.06639
100	0.05569
105	0.04265
110	0.04090
115	0.03568
120	0.03045
125	0.02671
130	0.02297
135	0.02026
140	0.01754
145	0.01555
150	0.01355

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

www.ametherm.com