

Inductors

Military, MIL/PRF/15305 Qualified, Type LT
Molded, Shielded



INDUCTANCE RANGE AND MILITARY STANDARD						
INDUCTANCE RANGE		CLASSIFICATION		MATERIAL		MILITARY STANDARD
FROM	TO	GRADE	CLASS	CORE	SHIELD	
0.10 μ H	0.82 μ H	1	A	Phenolic	Powd. Iron	MS75087
1.0 μ H	12.0 μ H	1	A	Powd. Iron	Powd. Iron	MS75088

ENVIRONMENTAL PERFORMANCE		
TEST	CONDITIONS	SPECIFICATIONS
Barometric Pressure	Test Condition C	MIL-STD-202, Method 105
Thermal Shock	Test Condition A-1	MIL-STD-202, Method 107
Flammability	-	MIL-STD-202, Method 111
Overload	-	MIL-PRF-15305
Low Temperature Storage	-	MIL-PRF-15305
Resistance to Soldering Heat	Test Condition A	MIL-STD-202, Method 210
Resistance to Solvents	-	MIL-STD-202, Method 215

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	IND. (μ H)	TOL.	MILITARY STANDARD	MILITARY TYPE	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ. MIN. (MHz)	DCR at 25 °C MAX. (Ohms)	RATED DC** CURRENT (mA)
MS75087	0.10	$\pm 10\%$	- 1	LT10K 191	50	25.0	250.0	0.025	1790
	0.12	$\pm 10\%$	- 2	192	51	25.0	250.0	0.034	1530
	0.15	$\pm 10\%$	- 3	193	51	25.0	250.0	0.037	1470
	0.18	$\pm 10\%$	- 4	194	50	25.0	250.0	0.047	1300
	0.22	$\pm 10\%$	- 5	195	49	25.0	250.0	0.067	1100
	0.27	$\pm 10\%$	- 6	196	47	25.0	250.0	0.11	855
	0.33	$\pm 10\%$	- 7	197	46	25.0	250.0	0.13	780
	0.39	$\pm 10\%$	- 8	198	44	25.0	250.0	0.18	670
	0.47	$\pm 10\%$	- 9	199	44	25.0	235.0	0.25	565
	0.56	$\pm 10\%$	- 10	200	43	25.0	210.0	0.33	490
	0.68	$\pm 10\%$	- 11	201	42	25.0	190.0	0.45	420
	0.82	$\pm 10\%$	- 12	202	40	25.0	180.0	0.59	370

* Measured with full length lead.

** **Rated DC Current:** Based on maximum temperature rise not to exceed 15 °C at + 90 °C ambient.

FEATURES

- Wide inductance range in small package
- Flame retardant coating
- Electromagnetic shield - finest shield available
- Epoxy molded construction provides superior moisture protection
- Precision performance, excellent reliability, sturdy construction

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: $\pm 10\%$ standard

Insulation Resistance: 1000 Megohm minimum per MIL-STD-202, Method 302, Test Condition B

Dielectric Withstanding Voltage: 1000 VAC per MIL-STD-202, Method 301 (sea level)

Percent Coupling: 3 % maximum per MIL-PRF-15305

Operating Temperature Range: - 55 °C to + 105 °C

MECHANICAL SPECIFICATIONS


Terminal Strength: 5 pounds pull per MIL-STD-202, Method 211, Test Condition A

Weight: 0.85 grams maximum

MATERIAL SPECIFICATIONS

Encapsulant: Epoxy

Standard Terminal: #22 AWG tinned copper





STANDARD ELECTRICAL SPECIFICATIONS									
MODEL	IND. (μH)	TOL.	MILITARY STANDARD	MILITARY TYPE	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ. MIN. (MHz)	DCR at 25 °C MAX. (Ohms)	RATED DC** CURRENT (mA)
MS75088	1.0	± 10 %	- 1	LT10K 203	44	25.0	140.0	0.07	1070
	1.2	± 10 %	- 2	204	44	7.9	130.0	0.10	895
	1.5	± 10 %	- 3	205	44	7.9	115.0	0.12	815
	1.8	± 10 %	- 4	206	44	7.9	105.0	0.14	775
	2.2	± 10 %	- 5	207	44	7.9	100.0	0.19	650
	2.7	± 10 %	- 6	208	44	7.9	92.0	0.28	535
	3.3	± 10 %	- 7	209	44	7.9	85.0	0.35	480
	3.9	± 10 %	- 8	210	44	7.9	75.0	0.40	450
	4.7	± 10 %	- 9	211	44	7.9	70.0	0.55	380
	5.6	± 10 %	- 10	212	44	7.9	65.0	0.72	335
	6.8	± 10 %	- 11	213	50	7.9	55.0	1.02	280
	8.2	± 10 %	- 12	214	50	7.9	50.0	1.32	250
	10.0	± 10 %	- 13	215	50	7.9	46.0	1.62	220
	12.0	± 10 %	- 14	216	55	2.5	44.0	2.0	200

* Measured with full length lead.

** **Rated DC Current:** Based on maximum temperature rise not to exceed 15 °C at + 90 °C ambient.

DESCRIPTION - MILITARY PART NUMBER						
MS75088	- 13	OR	LT	10	K	215
MILITARY STANDARD	INDUCTANCE VALUE		TYPE	GRADE AND CLASS	FAMILY	ID NUMBER

GLOBAL PART NUMBER INFORMATION											
M	S	7	5	0	8	8	-	1	3	R	U
MODEL						INDUCTANCE VALUE			PACKAGE CODE		



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.