

**DUAL GENERAL PURPOSE LOW VOLTAGE COMPARATOR****AZV393****Description**

The AZV393 is a low voltage 2.5V to 5.5V, dual comparator, which has a very low supply current of 100 μ A, making the part an excellent choice for portable electronic systems. The device is pin-for-pin compatible replacement of the LMV393.

The AZV393 is built with BiCMOS process with bipolar input and output stages for improved noise performance. It is a cost-effective solution for portable consumer products where space, low voltage, low power and price are the primary specification in circuit design.

The AZV393 is available in standard SOIC-8 and space saving TSSOP-8 and MSOP-8 packages.

Features

- Guaranteed 2.7V to 5.5V Performance
- Industrial Temperature Range: -40°C to 85°C
- Low Supply Current: 100 μ A Typical
- Input Common Mode Voltage Range Includes Ground
- Low Output Saturation Voltage: 200mV Typical
- Open Collector Output for Maximal Flexibility

Applications

- Notebook and PDA
- Low Power, Low Voltage Applications
- General Purpose Portable Devices
- Mobile Communications
- Battery Powered Electronics

Benefits

- Low Supply Voltage
- Low Supply Current
- Wide Input Common-Mode Voltage Range
- Low Output Saturation Voltage
- Small Package
- Very Competitive Price

Parametric Table

$V_{CC}=5V$, typical, unless otherwise specified


Supply Voltage Range (V)	2.5 to 5.5
Supply Current (μ A)	100
Input Offset Voltage (mV)	1.7
Input Offset Current (nA)	2
Input Bias Current (nA)	25
Voltage Gain (V/mV)	50
Input Common-Mode Voltage (V)	-0.1 to $V_{CC}-0.8$
Output Saturation Voltage (mV)	200
Propagation Delay (High to Low) (Input Overdrive=100mV) (ns)	200
Propagation Delay (Low to High) (Input Overdrive=100mV) (ns)	300
Operating Junction Temperature (°C)	-40 to 85
Package	SOIC-8 TSSOP-8 MSOP-8

Additional Available Materials

- Samples
- Preliminary Datasheet
- Reliability Report
- ESD Report

**DUAL GENERAL PURPOSE LOW VOLTAGE COMPARATOR****AZV393****Pin Configuration**

SOIC-8/TSSOP-8/MSOP-8

**Ordering Information Example**

Package	Temperature Range	Part Number	Marking ID	Packing Type
		Lead Free	Lead Free	
SOIC-8	-40 to 85°C	AZV393M-E1	AZV393M-E1	Tube
		AZV393MTR-E1	AZV393M-E1	Tape & Reel
TSSOP-8	-40 to 85°C	AZV393G-E1	EG3D	Tube
		AZV393GTR-E1	EG3D	Tape & Reel
MSOP-8	-40 to 85°C	AZV393MM-E1	AZV393MM-E1	Tube
		AZV393MMTR-E1	AZV393MM-E1	Tape & Reel

Detailed information please refer to the relevant datasheet.

Sales Office:**USA**

30920 Huntwood Ave. Hayward, CA 94544,
USA
Tel : +1-510-324-2988
Fax : +1-510-324-2788

Taiwan

4F, 298-1 Rui Guang Road, Nei-Hu District, Taipei,
Taiwan
Tel : 886-2-2656-2808
Fax : 886-2-2656-2806

Shanghai

8F, B Zone, 900 Yi Shan Road, Shanghai 200233,
China
Tel : 86-21-6495 9539
Fax : 86-21-6485 9673

Shenzhen

Room E, 5F, Noble Center, No.1006, 3rd Fuzhong Road, Futian
District, Shenzhen 518026, China
Tel : 86-755-8826 7951
Fax : 86-755-8826 7865