

**SOT-23 BIPOLAR TRANSISTORS
TRANSISTOR(PNP)**

FEATURES


- * Power dissipation
PCM : 0.2 W(Tamb=25°C)

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-O rate flame retardant
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 0.008 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



MAXIMUM RATINGS (@ TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	VALUE	UNITS
Collector-base voltage	V _{CB0}	-45	V
Collector-emitter voltage	V _{CE0}	-45	V
Emitter-base voltage	V _{EB0}	-7	V
Collector current-continuous	I _C	-200	mA
Junction and Storage temperature	T _J , T _{stg}	-55-150	°C

ELECTRICAL CHARACTERISTICS (@ TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	MIN	MAX	UNITS
Collector-base breakdown voltage (I _C = -10μA, I _E =0)	V _{(BR)CBO}	-45	-	V
Collector-emitter breakdown voltage (I _C = -2mA, I _B =0)	V _{(BR)CEO}	-45	-	V
Emitter-base breakdown voltage (I _E = -10μA, I _C =0)	V _{(BR)EBO}	-7	-	V
Collector cut-off current (V _{CB} = -20V, I _E =0)	I _{CBO}	-	-0.1	μA
Emitter cut-off current (V _{CE} = -10V, I _B =0)	I _{CEO}	-	-100	μA
DC current gain (V _{CE} = -10V, I _C = -2mA)	h _{FE}	160	460	-
Collector-emitter saturation voltage (I _C = -100mA, I _B = -10mA)	V _{CE(sat)}	-	-0.5	V
Transition frequency (V _{CE} = -10V, I _C = -1mA, f= 200MHz)	f _T	60	-	MHz
Collector output capacitance (V _{CB} = -10V, I _E = 0, f= 1MHz)	C _{ob}	-	2.7	pF

CLASSIFICATION OF h_{FE}

RANK	Q	R	S
Range	160-260	210-340	290-460
Marking	BQ1	BR1	BS1

RATING AND CHARACTERISTICS CURVES (2SB709A)




Figure1 P_C - T_A




Figure2 I_C - V_{CE}




Figure3 I_C - I_B




Figure4 I_B - V_{BE}




Figure5 I_C - V_{BE}

RATING AND CHARACTERISTICS CURVES (2SB709A)




Figure6 $V_{CE(sat)}-I_C$




Figure7 $h_{FE}-I_C$




Figure8 f_T-I_E




Figure9 $C_{ob}-V_{CB}$




Figure10 N_F-I_E

RATING AND CHARACTERISTICS CURVES (2SB709A)




Figure11 N_F-I_E




Figure12 h PARAMETER- I_E




Figure13 h PARAMETER- V_{CE}

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.