

# Voltage Controlled Oscillator Model HVA87T-3

## Model HVA87SM-32



Microwave Band 2.6 to 5.2 GHz

### Electrical Specifications:<sup>(1)</sup>




Parameter	Specifications
Frequency Range	2.6 to 5.2 GHz
Power Output at 25°C (50 Ohm load)	+12 dBm, min.
Power Output Variation vs. Temperature	2.0 dB, typical
Frequency Drift vs. Temperature <sup>(2)</sup>	75 MHz, typical
Frequency Pulling (12 dB Return Loss)	3.0 MHz, typical
Frequency Pushing	0.3 MHz/V, typical
Tuning Voltage Limits	0 to +18 VDC
SSB Phase Noise (50 kHz offset)	-92 dBc/Hz, typical
Harmonics <sup>(3)</sup>	-12 dBc, typical
Spurious	-70 dBc, max.
Bias Voltage <sup>(4)</sup>	+15 VDC ±1%
Bias Current <sup>(5)</sup>	100 mA, typical
Operating Temperature	-40 to +85°C

#### Notes:

- Specifications guaranteed over the operating temperature range. Those specifications indicated as typical are not guaranteed. Plots exemplify typical performance at +25°C
- Total frequency drift over the full temperature range.
- Worst case harmonics over the frequency range.
- Alternate bias voltages available.
- Lower bias current available.
- Military screening available.



### Typical Performance at 25°C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, FL 32905 · PH (888) 553-7531 · Fax (888) 553-7532

www.SpectrumMicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, PA 19154 · PH (215) 464-4000 · Fax (215) 464-4001