

# TSic™- 306

## High Precision, Rapid Response, Low Cost Temperature Sensor IC

### Feature Sheet


#### Features

- Low cost, precision temperature sensor
- Single-wire 11-bit digital serial signal output compatible with state-of-the-art  $\mu$ P controllers
- Communication range > 10 meters
- Resolution: 0.1°C
- Accuracy:  $\pm 0.3^\circ\text{C}$  over a span of 80°C
- Wide measurement range:  $-50$  to  $+150^\circ\text{C}$
- Signal read-out every 0.1s (other rates available on request)
- V+ supply voltage: 2.97 to 5.5V (industry standard); 3.3V or 5V ( $\pm 10\%$ ) power supplies
- Package: 8-pin SOIC
- Low quiescent current:  $< 80\mu\text{A}$  at  $25^\circ\text{C}$  with 3.3V – minimizes self-heating errors for applications such as wall-mounted thermostats
- System-on-a-chip based on advanced mixed-signal technology integrating precision temperature sensing bandgap reference with proportional-to-absolute-temperature (PTAT) output, digital signal processor (DSP) core, and electrically erasable memory (EEPROM)

#### Package Information

TSic™ 306 SOP8: 150mil, Standard SMT Package, SOIC, Based on IEC 191-2Q, Type 076E35 B.

Other packages available on demand: TSic™ 306 e-line; 3 pin THT package.



Pin	Name	Description
1	V+	Supply voltage (3.0-5.5V)
2	Signal	Temperature output signal
4	Gnd	Ground
3, 5-8	TP/NC	Test pin / NC Do not connect

#### Brief Description

The TSic™ temperature sensor IC family are fully tested and calibrated sensors with absolute measurement accuracy on delivery – no further calibration needed. The TSic™ combines outstanding accuracy with long term stability, yet it is very simple to use.

The TSic™ series is specifically designed for high performance, cost-effective solutions for sensing temperature in building automation, automotive, industrial, office automation, white goods and low-power/mobile applications.

TSic™ employs a high precision bandgap reference with PTAT output; a low-power, precision ADC; and an on-chip DSP core with EEPROM to precisely calibrate the output temperature signal. The TSic™ series includes ICs with two linear analog signal output options, such as standard 0~1Vout ( $V+ = 2.97\text{V}$  to  $5.5\text{V}$ ) or ratiometric (10~90% of  $V+$ ; i.e.,  $0.5\sim 4.5\text{Vout}$  @  $V+ = 5\text{V}$ ) or the digital serial output signal for interfacing with  $\mu$ P controllers.

#### Benefits

- **Several accuracy classes available with 100% upward compatibility**
- **No calibration by customer needed; absolute calibration specified**
- **Simple to integrate, reducing cost and time for application-development**
- **Fast data measurement – optimal for temperature control**
- **Packages for standard SMD, THT or application specific assembly**
- **Very low power consumption – ideal for mobile and standard applications**
- **Field reconfiguration/recalibration option available (high volume customers only)**
- **Outstanding long term stability**



INNOVATIVE SENSOR TECHNOLOGY



# TSic™- 306

High Precision, Rapid Response, Low Cost Temperature Sensor IC

## Feature Sheet

### Absolute Maximum Ratings

PARAMETER	MIN	TYP	MAX	UNITS
Supply Voltage (V <sub>+</sub> )	-0.3		6.0	V
Voltages at Analog I/O Pins (V <sub>INA</sub> , V <sub>OUTA</sub> )	-0.3		V <sub>DDA</sub> +0.3	V
Storage Temperature Range (T <sub>stor</sub> )	-50		150	°C

### Operating Conditions

PARAMETER	MIN	TYP	MAX	UNITS
Supply Voltage to Gnd (V <sub>+</sub> ) <sup>1</sup>	2.97	5.0	5.5	V
Supply Current (I <sub>v+</sub> ) @ V <sub>+</sub> = 3.3V, RT	30	45	80	μA
Ambient Temperature Range (T <sub>amb</sub> ) <sup>2</sup>	-50		150	°C
Output Load Capacitance (C <sub>L</sub> ) <sup>3</sup>		10	15	nF
External Capacitance Between V <sub>+</sub> and Gnd (C <sub>V+</sub> ) <sup>4</sup>	80	100	470	nF
Output Load Resistance (R <sub>L</sub> ) Signal to Gnd (or V <sub>+</sub> ) <sup>5</sup>	2.5	10		KΩ

- 1 With supply voltage 2.7V - 2.97V, accuracy is slightly reduced; below 2.7V, functionality is unknown.
- 2 Output signal is limited to this ambient temperature (applies to calibration, offset and gain).
- 3 When using the output as a digital output, the load capacitor C<sub>L</sub> is limited by maximum rise time for ZACwire™.
- 4 Locate as close as possible to TSic's V<sub>+</sub> and Gnd pins.
- 5 When using the output as a digital output, no pull-down resistor is allowed.

### For further information:

ZMD America, Inc.  
201 Old Country Road, Suite 204  
Melville, NY 11747, USA  
Phone +01 (631) 549-2666  
Fax +01 (631) 549-2882  
[sales@zmda.com](mailto:sales@zmda.com)  
[www.zmd.biz](http://www.zmd.biz)

ZMD AG  
Grenzstrasse 28  
01109 Dresden, Germany  
Tel.: +49 (0)351.8822.366  
Fax: +49 (0)351.8822.337  
[sales@zmd.de](mailto:sales@zmd.de)  
[www.zmd.biz](http://www.zmd.biz)

ZMD Far East  
Taipei World Center  
Sinyi Road, Sec. 5, Suite 7A-03  
Taipei 110, Taiwan  
Phone +886 (2) 8786 1592  
Fax +886 (2) 2723 3109  
[sales@zmd.de](mailto:sales@zmd.de)  
[www.zmd.biz](http://www.zmd.biz)



### Temperature Accuracy

PARAMETER	MIN	TYP	MAX	UNITS
<i>Wide Range Device for -50° to 150°C</i>				
+10 to 90 °C	-0.3	±0.3	0.3	°C <sup>1</sup>
-20 to +10, 90-110	-0.2	+0.3	0.95	°C <sup>1</sup>
-50 to -20, 110-150	0	+0.9	2.0	°C <sup>1</sup>

<sup>1</sup> 2s value, plus 1 bit quantization error (0.1°C).

Available on request: TSic™ products with customer-specific special calibration which shifts the 80°C span (bandgap) with the high precision temperature range of ±0.3 °C to a lower or higher temperature range.

### Output Examples for TSic™ Devices

		Temperature Measurement Range -50°C to 150°C or -58°F to 302°F (Wide Range Device)		
		TSic-301	TSic-303	TSic-306 <sup>1</sup>
Temp (°C)	Temp (°F)	Analog 0~1V	Analog ratiometric 10~90%	Digital <sup>1</sup>
-50	-58	0.000	10	<b>0x000</b>
-10	14	0.200	26	<b>0x199</b>
0	32	0.250	30	<b>0x200</b>
25	77	0.375	40	<b>0x2FF</b>
60	140	0.550	54	<b>0x465</b>
125	257	0.875	80	<b>0x6FE</b>
150	302	1.000	90	<b>0x7FF</b>

<sup>1</sup> Temperature = (Digital signal / 2047 \* 200 - 50) °C