



### Features

- Guard Ring Die Construction for Transient Protection
- Low Power Loss, High Efficiency
- High Surge Capability
- Very Low Forward Voltage Drop
- For Use in Low Voltage, High Frequency Inverters, Free Wheeling, and Polarity Protection Applications
- Lead Free Finish, RoHS Compliant (Note 2)**

### Mechanical Data

- Case: D<sup>2</sup>PAK
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish - Tin. Solderable per MIL-STD-202, Method 208 
- Polarity: See Diagram
- Marking: Type Number
- Ordering Information: See Page 2
- Weight: 1.7 grams (approximate)



D <sup>2</sup> PAK		
Dim	Min	Max
A	9.65	10.69
B	14.60	15.88
C	0.51	1.14
D	2.29	2.79
E	4.37	4.83
G	1.14	1.40
H	1.14	1.40
J	8.25	9.25
K	0.30	0.64
L	2.03	2.92
M	2.29	2.79
All Dimensions in mm		

### Maximum Ratings @ T<sub>A</sub> = 25 C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.

Characteristic	Symbol	SBG1025L	SBG1030L	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>	25	30	V
Working Peak Reverse Voltage	V <sub>RWM</sub>			
DC Blocking Voltage	V <sub>R</sub>			
RMS Reverse Voltage	V <sub>R(RMS)</sub>	18	21	V
Average Rectified Output Current @ T <sub>C</sub> = 120 C	I <sub>O</sub>	10		A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave Superimposed on Rated Load	I <sub>FSM</sub>	200		A
Typical Thermal Resistance Junction to Case (Note 1)	R <sub>JC</sub>	3.0		C/W
Operating Temperature Range	T <sub>J</sub>	-65 to +125		C
Storage Temperature Range	T <sub>STG</sub>	-65 to +150		C

### Electrical Characteristics @ T<sub>A</sub> = 25 C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Breakdown Voltage (Note 3)	V <sub>(BR)R</sub>	25			V	I <sub>R</sub> = 1mA
Forward Voltage	V <sub>FM</sub>		0.34	0.45	V	@ I <sub>F</sub> = 10A, T <sub>C</sub> = 25 C
				0.36		@ I <sub>F</sub> = 10A, T <sub>C</sub> = 125 C
				0.55		@ I <sub>F</sub> = 20A, T <sub>C</sub> = 25 C
				0.50		@ I <sub>F</sub> = 20A, T <sub>C</sub> = 125 C
Peak Reverse Current at Rated DC Blocking Voltage (Note 3)	I <sub>RM</sub>		150	260	mA	@ T <sub>C</sub> = 25 C @ T <sub>C</sub> = 125 C
Typical Total Capacitance	C <sub>T</sub>		350		pF	f = 1.0MHz, V <sub>R</sub> = 4.0V DC, Per Element

- Notes:
- Thermal resistance: junction to case mounted on heat sink.
  - RoHS revision 13.2.2003. High Temperature Solder Exemption Applied, See EU Directive Annex Note 7.
  - Short duration pulse test used to minimize self-heating effect.




Fig. 1 Forward Derating Curve




Fig. 2 Typical Forward Characteristics, Per Element




Fig. 3 Typical Reverse Characteristics, Per Element




Fig. 4 Maximum Non-Repetitive Surge Current




Fig. 5 Typical Total Capacitance, Per Element

## Ordering Information (Note 4)

Device	Packaging	Shipping
SBG1025L-F	D <sup>2</sup> PAK	50/Tube
SBG1025L-T-F	D <sup>2</sup> PAK	800/Tape & Reel
SBG1030L-F	D <sup>2</sup> PAK	50/Tube
SBG1030L-T-F	D <sup>2</sup> PAK	800/Tape & Reel

Notes: 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

## Marking Information



SBG10XXL = Product type marking code (SBG1025L or SBG1030L)  
 DII = Manufacturers' code marking  
 YWW = Date code marking  
 Y = Last digit of year ex: 2 for 2002  
 WW = Week code 01 to 52

### IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

### LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.