

TANTALUM ELECTROLYTIC CAPACITORS

TMF Series

Chip Tantalum Capacitor With face down Terminals

Features


- A new, originally designed structure with reduced space requirement, resulting in the small size and large capacitance of units.
- Best suited for multi-media applications, such as cell phones, digital video cameras, etc.
- Environmentally friendly terminal plating -- lead-free (100% Sn) solder plating.

Product code : (Example) TMF Series LM case 6.3V 22μF±20%

TMF LM 0J 226 M T R F

Type of series	Tinned plated terminals (Sn 100)
Case size code	Packing polarity code
	Packing method code (T: carrier tape)
	Capacitance tolerance code (M : ± 20%)
	Capacitance code
	Rated voltage code

Outline of drawings and dimensions



Dimensions

(Unit : mm)

Case code	Case size				
	L ^{±0.1}	W ^{±0.1}	H ^{±0.1}	l ^{±0.1}	a ^{±0.1}
LM	1.6	0.85	0.8	0.5	0.65
LP	2.0	1.25	0.9	0.5	0.90
LA	3.2	1.60	0.9	0.8	1.20

Standard value and case size

Capacitance μF	Rated voltage (V.DC)				
	2.5 0E	4 0G	6.3 0J	10 1A	16 1C
1.0	105				
1.5	155				
2.2	225				LM
3.3	335				LM
4.7	475				LP
6.8	685			LM	LP
10	106			LM	LA
15	156		LM	LP	LA
22	226	LM	LM	LP	
33	336	LM	LM	LP	LA
47	476	LM	LP	LP	LA
68	686	LP	LP	LA	
100	107	LP	LA	LA	
150	157	LA	LA		
220	227	LA			

Product specifications	TMF				Test conditions JIS C5101-1:1998												
Operating temperature range	−55°C ~ +125°C																
Rated voltage	DC2.5~16V				85°C												
Surge voltage	DC3.2~20V				85°C												
Derated voltage	DC1.6~10V				125°C												
Capacitance	2.2~220 μF																
Capacitance tolerance	±20%				Paragraph 4.7, 120 Hz												
Leakage current	Refer to standard product table				Paragraph 4.9, in 5 minutes after the rated voltage is applied.												
tanδ	0.3 or less				Paragraph 4.8, 120Hz												
Surge withstand voltage	△C/C ±20% or less tan δ Specified initial value or less LC Specified initial value or less				Paragraph 4.26												
Temperature characteristics	<table border="1"> <tr> <td>Specified initial value</td> <td>−55</td> <td>85</td> <td>125</td> </tr> <tr> <td>△C/C</td> <td>−20~+20%</td> <td>0~+20%</td> <td>0~+20%</td> </tr> <tr> <td>tan δ</td> <td>0.3</td> <td>0.6</td> <td>0.3</td> </tr> </table>				Specified initial value	−55	85	125	△C/C	−20~+20%	0~+20%	0~+20%	tan δ	0.3	0.6	0.3	Paragraph 4.24
Specified initial value	−55	85	125														
△C/C	−20~+20%	0~+20%	0~+20%														
tan δ	0.3	0.6	0.3														
Solder heat resistance	△C/C ±20% or less tan δ Specified initial value or less LC Specified initial value or less				Solder Dip 260±5°C 10±1 sec. Reflow 260°C 10±1 sec.												
Moisture resistance no load	△C/C ±20% or less tan δ 150% Specified initial value or less LC Specified initial value or less				Paragraph 4.22, 40°C 90 ~ 95%RH, 500hrs												
High-temperature load	△C/C ±20% or less tan δ Specified initial value or less LC 200% Specified initial value or less				Paragraph 4.23, 85°C The rated voltage is applied for 2000 hours.												
Thermal shock	△C/C ±20% or less tan δ Specified initial value or less LC Specified initial value or less				Leave at -55°C, normal temperature, 125°C, and normal temperature for 30 min., 3 min., 30 min., and 3 min. Repeat this operation 5 times running.												
Failure rate	1% / 1000hrs				85°C. The rated voltage is applied (through a protective resistor of 1 Ω/V).												

※This catalog is designed for providing general information. Please inquire of our Sales Department to confirm specifications prior to use.

TANTALUM ELECTROLYTIC CAPACITORS

Standard product tables - TMF series

Standard product tables - TMF series

Rated voltage V. DC	capacitance μF	tanδ	Leakage current μA	case code	Product name
2.5	33	0.30	8.2	LM	TMFLM0E336
	47	0.30	11.7	LM	TMFLM0E476
	68	0.30	17.0	LP	TMFLP0E686
	100	0.30	25.0	LP	TMFLP0E107
	150	0.30	37.5	LA	TMFLA0E157
	220	0.30	55.0	LA	TMFLA0E227
4	22	0.30	8.8	LM	TMFLM0G226
	33	0.30	13.2	LM	TMFLM0G336
	47	0.30	18.8	LP	TMFLP0G476
	68	0.30	27.2	LP	TMFLP0G686
	100	0.30	40.0	LA	TMFLA0G107
	150	0.30	60.0	LA	TMFLA0G157
6.3	15	0.30	9.4	LM	TMFLM0J156
	22	0.30	13.8	LM	TMFLM0J226
	33	0.30	20.7	LP	TMFLP0J336
	47	0.30	29.6	LP	TMFLP0J476
	68	0.30	42.8	LA	TMFLA0J686
	100	0.30	63.0	LA	TMFLA0J107
10	6.8	0.30	6.8	LM	TMFLM1A685
	10	0.30	10.0	LM	TMFLM1A106
	15	0.30	15.0	LP	TMFLP1A156
	22	0.30	22.0	LP	TMFLP1A226
	33	0.30	33.0	LA	TMFLA1A336
	47	0.30	47.0	LA	TMFLA1A476
16	2.2	0.30	3.5	LM	TMFLM1C225
	3.3	0.30	5.2	LM	TMFLM1C335
	4.7	0.30	7.5	LP	TMFLP1C475
	6.8	0.30	10.8	LP	TMFLP1C685
	10	0.30	16.0	LA	TMFLA1C106
	15	0.30	24.0	LA	TMFLA1C156

Marking indication TMF series

LM · LP case		①Anode indication belt mark ②Simplified code of rated voltage (J:6.3V) ③Simplified code of nominal capacitance (A:10μF)
LA case		①Anode indication belt mark ②Simplified code of rated voltage (G:4V) ③Simplified code of nominal capacitance (A8:100μF) ④Lot indication (A:for manufacturing in January, 2009)

Lot indication

Month Year	1	2	3	4	5	6	7	8	9	10	11	12
2009	A	B	C	D	E	F	G	H	J	K	L	M
2010	N	P	Q	R	S	T	U	V	W	X	Y	Z
2011	a	b	c	d	e	f	g	h	j	k	l	m
2012	n	p	q	r	s	t	u	v	w	x	y	z