



COLLECTOR CURRENT = 10 AMPS PNP TYPES - CONTINUED

Device No	Case	VCBO Volts	VCEO (sus) Volts	VEBO Volts	hFE		VCE	IC	VCE (sat)	VBE (sat)	@ IC	@ IB	θ_{JC} °C/W	Ft MHz
					Min	Max								
2N6228	TO-3	140	140	7	15	60	2	3	1	1.5	3	.3	1.2	1
2N6229	TO-3	100	100	7	25	100	2	5	1	2	7.5	.75	1.2	1
2N6230	TO-3	120	120	7	20	80	2	5	1	2	7.5	.75	1.2	1
2N6231	TO-3	140	140	7	15	60	2	5	1	2	7.5	.75	1.2	1
AP1015	TO-66	375	350	4	12	50	1	1.2	.5	1.6	1.2	.2	3.9	2
AP1016	TO-3	400	350	4	10	50	3	4	1.5	1.7	4	.8	1.5	3
AP1022	TO-61	325	300	6	20	60	5	5	2.5	2.5	10	2	2	20
AP1023	TO-3	350	300	4	10	50	3	4	1.5	1.7	4	.8	1.5	3
AP1033	TO-66	300	275	4	12	70	1	1.2	.5	1.6	1.2	.2	3.9	2
AP1034	TO-3	300	275	4	8	50	3	10	1.5	2.25	10	1.25	1	2.5
AP1037	TO-66	275	250	4	12	70	1	1.2	.5	1.6	1.2	.2	3.9	2
AP1038	TO-66	275	250	4	12	70	1	1.2	.5	1.6	1.2	.2	3.9	2
AP1038	TO-3	300	250	4	10	50	3	4	1.5	1.7	4	.8	1.5	3
AP1052	TO-61	220	200	6	15	120	5	5	.5	1.2	2	.2	2	60
AP1053	TO-3	225	200	4	10	50	3	10	1.5	2.25	10	1	1	2.5
AP1054	TO-3	250	200	4	10	50	3	3	1.5	1.7	3	.6	1.5	3
AP1064	TO-3	300	180	4	30	300	2	1	.65	1.4	5	.5	1.2	50
AP1065	TO-5	200	170	4	40	120	5	5	.6	1.5	5	.5	20	60
AP1073	TO-3	200	150	6	40	120	5	5	.6	1.5	5	.5	1.5	20
AP1074	TO-3	170	150	6	20	70	2	3	1.5	2.2	1.5	.15	1.2	20
AP1075	TO-33	150	150	8	1K	10K	5	5	1.5	2.5	5	.005	20	30
AP1076	TO-66/3	150	150	8	1K	10K	5	5	1.5	2.5	5	.005	4	30
AP1083	TO-3	160	140	6	20	70	4	3	1	1.7	3	.3	1.5	4
AP1087	TO-61	175	130	6	30	90	5	5	2.5	2.5	10	1	2	20
AP1097	TO-3	140	120	6	15	60	4	2	2	3	5	.63	1.75	4
AP1098	TO-3	140	120	6	15	60	4	5	1.4	2.2	.5	.5	1.5	4
AP1099	TO-5	150	120	4	40	120	5	5	.6	1.5	5	.5	20	60
AP1100	TO-3	150	120	6	12	60	2	4	.75	1.5	4	.4	1	4
AP1101	TO-3	150	120	4	10	100	2	10	1	2	10	1	1.25	80
AP1145	TO-61	80	60	6	40	120	5	5	.5	1.2	5	.5	2	30
AP1146	TO-61	120	80	6	40	120	5	5	.5	1.2	5	.5	2	30
AP1147	TO-5	100	80	4	40	120	5	5	.6	1.5	5	.5	25	60