

# MCS®-48

## EXPRESS

- 0°C to 70°C Operation

- -40°C to +85°C Operation

- 168 Hr. Burn-In

- |                  |         |
|------------------|---------|
| ■ 8048AH/8035AHL | ■ 8748H |
| ■ 8049AH/8039AHL | ■ 8243  |
| ■ 8050AH/8040AHL | ■ 8749H |

The new Intel EXPRESS family of single-component 8-bit microcomputers offers enhanced processing options to the familiar 8048AH/8035AHL, 8748H, 8049AH/8039AHL, 8749H, 8050AH/8040AHL Intel components. These EXPRESS products are designed to meet the needs of those applications whose operating requirements exceed commercial standards, but fall short of military conditions.

The EXPRESS options include the commercial standard and -40°C to +85°C operation with or without 168 ± 8 hours of dynamic burn-in at 125°C per MIL-STD-883, method 1015. Figure 1 summarizes the option marking designators and package selections.

For a complete description of 8048AH/8035AHL, 8748H, 8049AH/8039AHL, 8749H, 8040AHL and 8050AH features and operating characteristics, refer to the respective standard commercial grade data sheet. This document highlights only the electrical specifications which differ from the respective commercial part.

Temp Range °C	0-70	-40- + 85	0-70	-40- + 85
Burn In	0 Hrs	0 Hrs	168 Hrs	168 Hrs
P8048AH	TP8048AH	QP8048AH	LP8048AH	
D8048AH	TD8048AH	QD8048AH	LD8048AH	
D8748H	TD8748H	QD8748H	LD8748H	
P8035AHL	TP8035AHL	QP8035AHL	LP8035AHL	
D8035AHL	TD8035AHL	QD8035AHL	LD8035AHL	
P8049AH	TP8049AH	QP8049AH	LP8049AH	
D8049AH	TD8049AH	QD8049AH	LD8049AH	
D8749H	TD8749H	QD8749H	LD8749H	
P8039AHL	TP8039AHL	QP8039AHL	LP8039AHL	
D8039AHL	TD8039AHL	QD8039AHL	LD8039AHL	
P8050AH	TP8050AH	QP8050AH	LP8050AH	
D8050AH	TD8050AH	QD8050AH	LD8050AH	
P8040AHL	TP8040AHL	QP8040AHL	LP8040AHL	
D8040AHL	TD8040AHL	QD8040AHL	LD8040AHL	
P8243	TP8243	QP8243		
D8243	TD8243	QD8243		LD8243

\* Commercial Grade  
 P Plastic Package  
 D Cerdip Package

*Extended Temperature Electrical Specification Deviations\**

TP8048AH/TP8035AHL/LP8048AH/LP8035AHL  
 TD8048AH/TD8035AHL/LD8048AH/LD8035AHL

**D.C. CHARACTERISTICS**  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ;  $V_{CC} = V_{DD} = 5V \pm 10\%$ ;  $V_{SS} = 0V$ 

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
$V_{IH}$	Input High Voltage (All Except XTAL1, XTAL2, RESET)	2.2		$V_{CC}$	V	
$I_{DD}$	$V_{DD}$ Supply Current		4	8	mA	
$I_{DD} + I_{CC}$	Total Supply Current		40	80	mA	

1

TP8049AH/TP8039AHL/LP8049AH/LP8039AHL  
 TD8049AH/TD8039AHL/LD8049AH/LD8039AHL

**D.C. CHARACTERISTICS**  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ;  $V_{CC} = V_{DD} = 5V \pm 10\%$ ;  $V_{SS} = 0V$ 

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
$V_{IH}$	Input High Voltage (All Except XTAL1, XTAL2, RESET)	2.2		$V_{CC}$	V	
$I_{DD}$	$V_{DD}$ Supply Current		5	10	mA	
$I_{DD} + I_{CC}$	Total Supply Current		50	100	mA	

TP8050AH/TP8040AHL/LP8050AHL/LP8040AHL  
 TD8050AH/TD8040AHL/LD8050AH/LD8040AHL

**D.C. CHARACTERISTICS**  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ;  $V_{CC} = V_{DD} = 5V \pm 10\%$ ;  $V_{SS} = 0V$ 

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
$V_{IH}$	Input High Voltage (All Except XTAL1, XTAL2, RESET)	2.2		$V_{CC}$	V	
$I_{DD}$	$V_{DD}$ Supply Current		10	20	mA	
$I_{DD} + I_{CC}$	Total Supply Current		75	120	mA	

***Extended Temperature Electrical Specification Deviations\****
**TD8748H/LD8748H**
**D.C. CHARACTERISTICS**  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ;  $V_{CC} = V_{DD} = 5V \pm 10\%$ ;  $V_{SS} = 0V$ 

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
$V_{IH}$	Input High Voltage (All Except XTAL1, XTAL2, RESET)	2.2		$V_{CC}$	V	
$I_{DD} + I_{CC}$	Total Supply Current		50	130	mA	

**TD8749H/LD8749H**
**D.C. CHARACTERISTICS**  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ;  $V_{CC} = V_{DD} = 5V \pm 10\%$ ;  $V_{SS} = 0V$ 

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
$V_{IH}$	Input High Voltage (All Except XTAL1, XTAL2, RESET)	2.2		$V_{CC}$	V	
$I_{DD} + I_{CC}$	Total Supply Current		75	150	mA	

**TP8743/TD8243/LD8243**
**D.C. CHARACTERISTICS**  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ;  $V_{CC} = 5V \pm 10\%$ ;  $V_{SS} = 0V$ 

Symbol	Parameter	Limits			Unit	Test Conditions
		Min	Typ	Max		
$I_{CC}$	$V_{CC}$ Supply Current		15	25	mA	

\*Refer to individual commercial grade data sheet for complete operating characteristics.