



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

SCHOTTKY BARRIER DIODE

VOLTAGE 30 Volts CURRENT 0.1 Ampere

Lead free devices

CH801H-30PT

APPLICATION

- * Low power rectification

FEATURE

- * Small surface mounting type. (SC-76/SOD-323)
- * Low VF. (VF=0.37V Typ. at 100mA)
- * High reliability


CONSTRUCTION

- * Silicon epitaxial planar



MARKING

- * JS

CIRCUIT



SC-76/SOD-323



Dimensions in millimeters

SC-76/SOD-323

MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	CH801H-30PT	UNITS
Maximum Recurrent Peak Reverse Voltage	VR _{RM}	30	Volts
Maximum RMS Voltage	V _{RMS}	21	Volts
Maximum DC Blocking Voltage	V _D C	30	Volts
Maximum Average Forward Rectified Current	I _O	0.1	Amps
Peak Forward Surge Current at 10 mSec single half sine-wave	I _{FSM}	1.0	Amps
Typical Junction Capacitance between Terminal (Note 1)	C _J	6.0	pF
Maximum Operating Temperature Range	T _J	-40 to +125	°C
Storage Temperature Range	T _{STG}	-55 to +125	°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	CH801H-30PT	UNITS
Maximum Instantaneous Forward Voltage at I _F = 100mA at I _F = 1.0 mA	V _F	0.45	Volts
		0.37	Volts
Maximum Average Reverse Current at V _R = 30V	I _R	1.0	uAmps

NOTES : 1. Measured at 1.0 MHz and applied reverse voltage of 10.0 volts.
2. ESD sensitive product handling required.

2002-5

RATING CHARACTERISTIC CURVES (CH801H-30PT)

FIG. 1 - FORWARD CHARACTERISTICS




FIG. 2 - REVERSE CHARACTERISTICS




FIG. 3 - TYPICAL JUNCTION CAPACITANCE




FIG. 4 - TYPICAL FORWARD CURRENT DERATING CURVE

