

SPECIFICATION SHEET

JFW MODEL 75R-089

ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2200 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-60 dB in 10 dB steps
VSWR	1.4:1 maximum DC-1000 MHz 1.6:1 maximum 1000-2200 MHz
Insertion Loss	0.3 dB maximum DC-1000 MHz 0.5 dB maximum 1000-2200 MHz
Attenuation Accuracy	± 0.5 or 2% DC-1000 MHz ± 0.5 or 3% 1000-2200 MHz
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Counter-Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC or F female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-003-01 (BNC) 092-003-02 (F) 092-003-03 (F/BNC) 092-003-04 (N)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/01/2000			17378	07/02/2009	C	TRS 07/02/2009
9999	05/20/2003	A					
4495	02/27/2004	B	CLV 02/27/2004				