



SPECIFICATIONS

STANDARD SPECIFICATIONS: ELECTRICAL
 DETECTORS TESTED USING 50V/mm ACROSS THE DETECTOR AND A 0.5MΩ LOAD RESISTOR IN SERIES.

	MIN.	TYP.	MAX.	UNITS
WAVELENGTH OF MAX. RESPONSE	2.2	2.4		μm
D*(500K, 650Hz, 1Hz)	7.5x10 ⁸	9.4x10 ⁸		cm Hz ² W ⁻¹
D*(pk, 650Hz, 1Hz)	8.0x10 ¹⁰	1.0x10 ¹¹		cm Hz ² W ⁻¹
ELEMENT RESISTANCE (DARK)	0.5	1	2	MΩ/sq.
TIME CONSTANT (NOT MEASURED)		200	400	μs
RATED ELEMENT TEMP.			65	°C
ELEMENT SIZE		1x1		mm
RESPONSMITY (pk, 650) vw-1	5.3x10 ⁵	8.0x10 ⁵		
AMBIENT TEMP./DETECTOR OPER. TEMP.		23		°C

PIN FUNCTION TABLE

PIN NO.	FUNCTION	COLOR
1	DETECTOR	BARE
2	CASE GND	BARE
3	DETECTOR	BARE

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= ^{+DECIMAL PRECISION} _{-0.00} MAX.= ^{+0.00} _{-DECIMAL PRECISION}



290 E. HELEN ROAD
 PALATINE, IL 60067-6976
 PHONE: +1.847.359.2790
 FAX: +1.847.359.6538
 WEB: WWW.LUMEX.COM

AMBIENT PbS 1x1

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
 THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE:	02.10.11	DRAWN BY:	AB
PAGE:	1 OF 1	CHKD BY:	KF
SCALE:	NTS	APRVD BY:	BC
UNIT:	mm [INCH]		Ⓟ