


**Full - Bridge
NPT & Trench + Field Stop® IGBT
Power module**


Trench & Field Stop® IGBT Q1, Q3:
 $V_{CES} = 600V$; $I_C = 50A$ @ $T_c = 80^\circ C$

Fast NPT IGBT Q2, Q4:
 $V_{CES} = 600V$; $I_C = 50A$ @ $T_c = 80^\circ C$



Top switches : Trench + Field Stop IGBT®

Bottom switches : FAST NPT IGBT



All multiple inputs and outputs must be shorted together

13/14 ; 15/16 ; 26/27 ; 31/32

Application

- Solar converter

Features

- **Q_2, Q_4 FAST Non Punch Through (NPT) IGBT**
 - Switching frequency up to 100 kHz
 - RBSOA & SCSOA rated
 - Low tail current
- **Q_1, Q_3 Trench & Field Stop IGBT®**
 - Low voltage drop
 - Switching frequency up to 20 kHz
 - RBSOA & SCSOA rated
 - Low tail current

- Kelvin emitter for easy drive
- Very low stray inductance
- High level of integration
- Internal thermistor for temperature monitoring

Benefits

- Optimized conduction & switching losses
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- Easy paralleling due to positive T_c of V_{CEsat}
- RoHS Compliant

 **CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handing Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

1. Top switches

1.1 Top Trench + Field Stop IGBT® characteristics

Absolute maximum ratings

Symbol	Parameter		Max ratings	Unit
V_{CES}	Collector - Emitter Breakdown Voltage		600	V
I_C	Continuous Collector Current	$T_C = 25^\circ\text{C}$	80	A
		$T_C = 80^\circ\text{C}$	50	
I_{CM}	Pulsed Collector Current	$T_C = 25^\circ\text{C}$	100	
V_{GE}	Gate – Emitter Voltage		± 20	V
P_D	Maximum Power Dissipation	$T_C = 25^\circ\text{C}$	176	W
RBSOA	Reverse Bias Safe Operating Area	$T_J = 150^\circ\text{C}$	100A @ 550V	

Electrical Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I_{CES}	Zero Gate Voltage Collector Current	$V_{GE} = 0\text{V}$, $V_{CE} = 600\text{V}$			250	μA
$V_{CE(\text{sat})}$	Collector Emitter Saturation Voltage	$V_{GE} = 15\text{V}$	$T_J = 25^\circ\text{C}$	1.5	1.9	V
		$I_C = 50\text{A}$	$T_J = 150^\circ\text{C}$	1.7		
$V_{GE(\text{th})}$	Gate Threshold Voltage	$V_{GE} = V_{CE}$, $I_C = 600\mu\text{A}$	5.0	5.8	6.5	V
I_{GES}	Gate – Emitter Leakage Current	$V_{GE} = 20\text{V}$, $V_{CE} = 0\text{V}$			600	nA

Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{ies}	Input Capacitance	$V_{GE} = 0\text{V}$ $V_{CE} = 25\text{V}$ $f = 1\text{MHz}$		3150		pF
C_{oes}	Output Capacitance			200		
C_{res}	Reverse Transfer Capacitance			95		
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching (25°C) $V_{GE} = \pm 15\text{V}$ $V_{Bus} = 300\text{V}$ $I_C = 50\text{A}$ $R_G = 8.2\Omega$		110		ns
T_r	Rise Time			45		
$T_{d(off)}$	Turn-off Delay Time			200		
T_f	Fall Time			40		
$T_{d(on)}$	Turn-on Delay Time			120		ns
T_r	Rise Time	$V_{GE} = \pm 15\text{V}$ $V_{Bus} = 300\text{V}$ $I_C = 50\text{A}$ $R_G = 8.2\Omega$		50		
$T_{d(off)}$	Turn-off Delay Time			250		
T_f	Fall Time			60		
E_{on}	Turn-on Switching Energy	$V_{GE} = \pm 15\text{V}$	$T_j = 25^\circ\text{C}$	0.3		mJ
		$V_{Bus} = 300\text{V}$	$T_j = 150^\circ\text{C}$	0.43		
E_{off}	Turn-off Switching Energy	$I_C = 50\text{A}$	$T_j = 25^\circ\text{C}$	1.35		mJ
		$R_G = 8.2\Omega$	$T_j = 150^\circ\text{C}$	1.75		
R_{thJC}	Junction to Case Thermal resistance				0.85	$^\circ\text{C}/\text{W}$

1.2 Top fast diode characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
V _{RRM}	Maximum Peak Repetitive Reverse Voltage			600			V
I _{RM}	Maximum Reverse Leakage Current	V _R =600V	T _j = 25°C			25	μA
			T _j = 125°C			500	
I _F	DC Forward Current		T _c = 80°C		30		A
V _F	Diode Forward Voltage	I _F = 30A			1.8	2.3	V
		I _F = 60A			2.1		
		I _F = 30A	T _j = 125°C		1.5		
t _{rr}	Reverse Recovery Time	I _F = 30A V _R = 400V di/dt = 200A/μs	T _j = 25°C		25		ns
			T _j = 125°C		160		
Q _{rr}	Reverse Recovery Charge		T _j = 25°C		35		nC
			T _j = 125°C		480		
R _{thJC}	Junction to Case Thermal resistance					1.2	°C/W

2. Bottom switches

2.1 Bottom Fast NPT IGBT characteristics

Absolute maximum ratings

Symbol	Parameter	Max ratings	Unit
V _{CES}	Collector - Emitter Breakdown Voltage	600	V
I _C	Continuous Collector Current	T _C = 25°C	65
		T _C = 80°C	50
I _{CM}	Pulsed Collector Current	T _C = 25°C	230
V _{GE}	Gate – Emitter Voltage	±20	V
P _D	Maximum Power Dissipation	T _C = 25°C	250
RBSOA	Reverse Bias Safe Operating Area	T _j = 125°C	100A @ 500V

Electrical Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
I _{CES}	Zero Gate Voltage Collector Current	V _{GE} = 0V	T _j = 25°C			250	μA
		V _{CE} = 600V	T _j = 125°C			500	
V _{CE(sat)}	Collector Emitter Saturation Voltage	V _{GE} = 15V I _C = 50A	T _j = 25°C	1.7	2.0	2.45	V
			T _j = 125°C		2.2		
V _{GE(th)}	Gate Threshold Voltage	V _{GE} = V _{CE} , I _C = 1mA		4		6	V
I _{GES}	Gate – Emitter Leakage Current	V _{GE} = 20V, V _{CE} = 0V				400	nA

Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C _{ies}	Input Capacitance	V _{GE} = 0V V _{CE} = 25V f = 1MHz	2200			pF
C _{oes}	Output Capacitance		323			
C _{res}	Reverse Transfer Capacitance		200			
Q _g	Total gate Charge	V _{GE} = 15V V _{Bus} = 300V I _C = 50A	166			nC
Q _{ge}	Gate – Emitter Charge		20			
Q _{gc}	Gate – Collector Charge		100			
T _{d(on)}	Turn-on Delay Time	Inductive Switching (25°C) V _{GE} = 15V V _{Bus} = 400V I _C = 50A R _G = 2.7Ω	40			ns
T _r	Rise Time		9			
T _{d(off)}	Turn-off Delay Time		120			
T _f	Fall Time		12			
T _{d(on)}	Turn-on Delay Time	Inductive Switching (125°C) V _{GE} = 15V V _{Bus} = 400V I _C = 50A R _G = 2.7Ω	42			ns
T _r	Rise Time		10			
T _{d(off)}	Turn-off Delay Time		130			
T _f	Fall Time		21			
E _{on}	Turn-on Switching Energy	V _{GE} = 15V V _{Bus} = 400V I _C = 50A R _G = 2.7Ω	T _j = 125°C	0.5		mJ
E _{off}	Turn-off Switching Energy		T _j = 125°C	1		
R _{thJC}	Junction to Case Thermal resistance				0.5	°C/W

2.2 Bottom diode characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
V _{RRM}	Maximum Peak Repetitive Reverse Voltage	V _R =600V	600			V
I _{RM}	Maximum Reverse Leakage Current		T _j = 25°C		25	μA
I _F	DC Forward Current	I _F = 30A I _F = 60A I _F = 30A	T _c = 80°C	30		A
V _F	Diode Forward Voltage		T _j = 125°C	1.8	2.3	V
			T _j = 125°C	2.1		
t _{rr}	Reverse Recovery Time	I _F = 30A V _R = 400V di/dt = 200A/μs	T _j = 25°C	25		ns
			T _j = 125°C	160		
Q _{rr}	Reverse Recovery Charge		T _j = 25°C	35		nC
			T _j = 125°C	480		
R _{thJC}	Junction to Case Thermal resistance				1.2	°C/W

3. Temperature sensor

NTC (see application note APT0406 on www.microsemi.com for more information).

Symbol	Characteristic	Min	Typ	Max	Unit
R ₂₅	Resistance @ 25°C		50		kΩ
B _{25/85}	T ₂₅ = 298.15 K		3952		K


$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]} \quad T: \text{Thermistor temperature} \\ R_T: \text{Thermistor value at } T$$

4. Package characteristics

Symbol	Characteristic		Min	Typ	Max	Unit
V _{ISOL}	RMS Isolation Voltage, any terminal to case t = 1 min, I _{isol} <1mA, 50/60Hz		2500			V
T _J	Operating junction temperature range		-40		150*	°C
T _{STG}	Storage Temperature Range		-40		125	
T _C	Operating Case Temperature		-40		100	
Torque	Mounting torque	To heatsink	M4	2.5	4.7	N.m
Wt	Package Weight				110	g

T_j=175°C for Trench & Field Stop IGBT


5. SP3 Package outline (dimensions in mm)




See application note 1901 - Mounting Instructions for SP3 Power Modules on www.microsemi.com


6. Top switches curves

6.1 Top Trench + Field Stop IGBT® typical performance curves





















6.2 Top Fast diode typical performance curves




7. Bottom switches curves


7.1 Bottom fast NPT IGBT typical performance curves







7.2 Bottom diode typical performance curves



Microsemi reserves the right to change, without notice, the specifications and information contained herein

Microsemi's products are covered by one or more of U.S patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents pending. All Rights Reserved.