

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.


TELEPHONE: (201) 376-29
(212) 227-60
FAX: (201) 376-89

1N1313A

REF/REG DIODE, 0W < P(D) ≤ 250MW

Description: Ref/Reg Diode, 0W < P(D) ≤ 250mW

Manufacturer.....	many
Mil/High-Rel? (Y/N).....	
Nom. Ref. Volt.....	8.75
Test Current.....	200u
Tol. (%).....	5
PD Max. (W).....	150m
Dyn. Zmax (j).....	
Temp Coef pp/10k.....	
Oper. Temp (x°C) Max.....	150
Pkg Style.....	
Surface Mounted (Y/N).....	N



1. PACKAGE CONTOUR OPTIONAL WITHIN DIMENSIONS A & B. SLUGS, IF ANY, SHALL BE INCLUDED WITHIN THIS CYLINDER BUT SHALL NOT BE SUBJECT TO THE MINIMUM LIMIT OF DIM. A.
2. LEAD DIAMETER NOT CONTROLLED IN THIS ZONE TO ALLOW FOR FLASH, LEAD FINISH BUILD-UP, AND MINOR IRREGULARITIES OTHER THAN SLUGS.

