


## Lead (Pb)-free Thick Film, Rectangular, Precision Chip Resistors



### FEATURES

- Low temperature coefficient (25 ppm/K) and tight tolerances ( $\pm 0.25\%$ )
- Metal glaze on high quality ceramic
- Protective overglaze
- Lead (Pb)-free solder contacts on Ni barrier layer
- Pure tin plating provides compatibility with lead (Pb)-free and lead containing soldering processes
- Compatible with "Restriction of the use of Hazardous Substances" (RoHS) directive 2002/95/EC (issue 2004)
- Excellent stability ( $\Delta R/R \leq \pm 1\%$  for 1000 h at 70 °C) in different environmental conditions



### STANDARD ELECTRICAL SPECIFICATIONS

MODEL	SIZE		POWER RATING $P_{70\text{ }^\circ\text{C}}$ W	LIMITING ELEMENT VOLTAGE MAX. V $\Xi$	TEMPERATURE COEFFICIENT ppm/K	TOLERANCE %	RESISTANCE RANGE $\Omega$	E-SERIES
	INCH	METRIC						
D10/CRCW0402-P	0402	1005	0.063	50	$\pm 100$	$\pm 0.5$	10R - 1M0	24 + 96
					$\pm 50$	$\pm 0.25; \pm 0.5; \pm 1$	100R - 1M0	
					$\pm 25$	$\pm 0.5; \pm 1$	1K0 - 10K	
D11/CRCW0603-P	0603	1608	0.1	75	$\pm 100$	$\pm 0.5$	10R - 10M	24 + 96
					$\pm 50$	$\pm 0.5; \pm 1$	100R - 10M	
					$\pm 25$	$\pm 0.25$	100R - 1M0	
D12/CRCW0805-P	0805	2012	0.125	150	$\pm 100$	$\pm 0.5$	10R - 10M	24 + 96
					$\pm 50$	$\pm 0.5; \pm 1$	100R - 10M	
					$\pm 25$	$\pm 0.25$	100R - 1M0	
D25/CRCW1206-P	1206	3216	0.25	200	$\pm 100$	$\pm 0.5$	10R - 10M	24 + 96
					$\pm 50$	$\pm 0.5; \pm 1$	100R - 10M	
					$\pm 25$	$\pm 0.25$	100R - 1M0	
CRCW1210-P	1210	3225	0.33	200	$\pm 100$	$\pm 0.5$	10R - 10M	24 + 96
					$\pm 50$	$\pm 0.5; \pm 1$	100R - 1M0	
					$\pm 25$	$\pm 0.25$	100R - 1M0	
CRCW1218-P	1218	3246	1.0	200	$\pm 100$	$\pm 0.5$	10R - 10M	24 + 96
					$\pm 50$	$\pm 0.5; \pm 1$	100R - 2M2	
					$\pm 25$	$\pm 0.25$	100R - 1M0	
CRCW2010-P	2010	5025	0.5	400	$\pm 100$	$\pm 0.5$	10R - 10M	24 + 96
					$\pm 50$	$\pm 0.5; \pm 1$	100R - 10M	
					$\pm 25$	$\pm 0.25$	100R - 1M0	
CRCW2512-P	2512	6332	1.0	500	$\pm 100$	$\pm 0.5$	10R - 10M	24 + 96
					$\pm 50$	$\pm 0.5; \pm 1$	100R - 10M	
					$\pm 25$	$\pm 0.25$	100R - 1M0	

### Notes

- These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.
- Marking and packaging: See appropriate catalog or web pages
- Power rating depends on the max. temperature at the solder point, the component placement density and the substrate material



Lead (Pb)-free Thick Film, Rectangular,  
Precision Chip Resistors

TECHNICAL SPECIFICATIONS									
PARAMETER	UNIT	D10/ CRCW0402-P	D11/ CRCW0603-P	D12/ CRCW0805-P	D25/ CRCW1206-P	CRCW1210-P	CRCW1218-P	CRCW2010-P	CRCW2512-P
Rated Dissipation at 70 °C (3)	W	0.063	0.1	0.125	0.25	0.33	1.0	0.5	1.0
Limiting Element Voltage (2)	V <sub>≅</sub>	50	75	150	200	200	200	400	500
Insulation Voltage (1 min)	V <sub>peak</sub>	> 75	> 100	> 200	> 300	> 300	> 300	> 300	> 300
Thermal Resistance (1)	K/W	≤ 870	≤ 550	≤ 440	≤ 220	≤ 140	≤ 65	≤ 88	≤ 65
Insulation Resistance	Ω	> 10 <sup>9</sup>							
Category Temperature Range	°C	- 55 to + 155							
Failure Rate	h <sup>-1</sup>	0.3 x 10 <sup>-9</sup>							
Weight/1000 pieces	g	0.65	2	5.5	10	16	29.5	25.5	40.5

Notes

- (1) For sizes 0402 until 1206 the measuring conditions are in acc. to EN 140401-802. For all other sizes the result depends on the solder pad dimensions.
- (2) Rated voltage:  $\sqrt{P \times R}$
- (3) The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heat flow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature of 155 °C is not exceeded.



PART NUMBER AND PRODUCT DESCRIPTION																																										
PART NUMBER: CRCW040275R0DKEDP (4)																																										
<table border="1" style="width:100%; text-align:center;"> <tr> <td>C</td><td>R</td><td>C</td><td>W</td><td>0</td><td>4</td><td>0</td><td>2</td><td>7</td><td>5</td><td>R</td><td>0</td><td>D</td><td>K</td><td>E</td><td>D</td><td>P</td><td></td> </tr> </table>							C	R	C	W	0	4	0	2	7	5	R	0	D	K	E	D	P																			
C	R	C	W	0	4	0	2	7	5	R	0	D	K	E	D	P																										
<table border="1"> <tr><th>MODEL</th></tr> <tr><td>CRCW0402</td></tr> <tr><td>CRCW0603</td></tr> <tr><td>CRCW0805</td></tr> <tr><td>CRCW1206</td></tr> <tr><td>CRCW1210</td></tr> <tr><td>CRCW1218</td></tr> <tr><td>CRCW2010</td></tr> <tr><td>CRCW2512</td></tr> </table>	MODEL	CRCW0402	CRCW0603	CRCW0805	CRCW1206	CRCW1210	CRCW1218	CRCW2010	CRCW2512	<table border="1"> <tr><th>VALUE</th></tr> <tr><td>R = Decimal</td></tr> <tr><td>K = Thousand</td></tr> <tr><td>M = Million</td></tr> </table>	VALUE	R = Decimal	K = Thousand	M = Million	<table border="1"> <tr><th>TOLERANCE</th></tr> <tr><td>C = ± 0.25 %</td></tr> <tr><td>D = ± 0.5 %</td></tr> <tr><td>F = ± 1.0 %</td></tr> </table>	TOLERANCE	C = ± 0.25 %	D = ± 0.5 %	F = ± 1.0 %	<table border="1"> <tr><th>TCR</th></tr> <tr><td>E = ± 25 ppm/K</td></tr> <tr><td>H = ± 50 ppm/K</td></tr> <tr><td>K = ± 100 ppm/K</td></tr> </table>	TCR	E = ± 25 ppm/K	H = ± 50 ppm/K	K = ± 100 ppm/K	<table border="1"> <tr><th>PACKAGING (5)</th></tr> <tr><td>EA, EB,</td></tr> <tr><td>EC, ED,</td></tr> <tr><td>EE, EI,</td></tr> <tr><td>EL, EK,</td></tr> <tr><td>EF, EG,</td></tr> <tr><td>EH, EY</td></tr> </table>	PACKAGING (5)	EA, EB,	EC, ED,	EE, EI,	EL, EK,	EF, EG,	EH, EY	<table border="1"> <tr><th>SPECIAL</th></tr> <tr><td>Up to 2 digits</td></tr> <tr><td>P = Precision</td></tr> </table>	SPECIAL	Up to 2 digits	P = Precision						
MODEL																																										
CRCW0402																																										
CRCW0603																																										
CRCW0805																																										
CRCW1206																																										
CRCW1210																																										
CRCW1218																																										
CRCW2010																																										
CRCW2512																																										
VALUE																																										
R = Decimal																																										
K = Thousand																																										
M = Million																																										
TOLERANCE																																										
C = ± 0.25 %																																										
D = ± 0.5 %																																										
F = ± 1.0 %																																										
TCR																																										
E = ± 25 ppm/K																																										
H = ± 50 ppm/K																																										
K = ± 100 ppm/K																																										
PACKAGING (5)																																										
EA, EB,																																										
EC, ED,																																										
EE, EI,																																										
EL, EK,																																										
EF, EG,																																										
EH, EY																																										
SPECIAL																																										
Up to 2 digits																																										
P = Precision																																										
PRODUCT DESCRIPTION: D10/CRCW0402-P 100 75R 0.5 % ET7 e3																																										
<table border="1"> <tr><th>D10/CRCW0402-P</th></tr> <tr><td>MODEL</td></tr> <tr><td>D10/CRCW0402-P</td></tr> <tr><td>D11/CRCW0603-P</td></tr> <tr><td>D12/CRCW0805-P</td></tr> <tr><td>D25/CRCW1206-P</td></tr> <tr><td>CRCW1210-P</td></tr> <tr><td>CRCW1218-P</td></tr> <tr><td>CRCW2010-P</td></tr> <tr><td>CRCW2512-P</td></tr> </table>	D10/CRCW0402-P	MODEL	D10/CRCW0402-P	D11/CRCW0603-P	D12/CRCW0805-P	D25/CRCW1206-P	CRCW1210-P	CRCW1218-P	CRCW2010-P	CRCW2512-P	<table border="1"> <tr><th>100</th></tr> <tr><td>TCR</td></tr> <tr><td>± 25 ppm/K</td></tr> <tr><td>± 50 ppm/K</td></tr> <tr><td>± 100 ppm/K</td></tr> </table>	100	TCR	± 25 ppm/K	± 50 ppm/K	± 100 ppm/K	<table border="1"> <tr><th>75R</th></tr> <tr><td>RESISTANCE VALUE</td></tr> <tr><td>49K9 = 49.9 kΩ</td></tr> <tr><td>5R1 = 5.1 Ω</td></tr> </table>	75R	RESISTANCE VALUE	49K9 = 49.9 kΩ	5R1 = 5.1 Ω	<table border="1"> <tr><th>0.5 %</th></tr> <tr><td>TOLERANCE</td></tr> <tr><td>± 0.25 %</td></tr> <tr><td>± 0.5 %</td></tr> <tr><td>± 1.0 %</td></tr> </table>	0.5 %	TOLERANCE	± 0.25 %	± 0.5 %	± 1.0 %	<table border="1"> <tr><th>ET7</th></tr> <tr><td>PACKAGING (5)</td></tr> <tr><td>ET1, ET5</td></tr> <tr><td>ET6, ET7</td></tr> <tr><td>EF4, EG1</td></tr> <tr><td>E20, ET0</td></tr> <tr><td>E02, E67</td></tr> <tr><td>E82, E27</td></tr> </table>	ET7	PACKAGING (5)	ET1, ET5	ET6, ET7	EF4, EG1	E20, ET0	E02, E67	E82, E27	<table border="1"> <tr><th>e3</th></tr> <tr><td>LEAD (Pb)-FREE</td></tr> <tr><td>e3 = Pure tin</td></tr> <tr><td>Termination finish</td></tr> </table>	e3	LEAD (Pb)-FREE	e3 = Pure tin	Termination finish	
D10/CRCW0402-P																																										
MODEL																																										
D10/CRCW0402-P																																										
D11/CRCW0603-P																																										
D12/CRCW0805-P																																										
D25/CRCW1206-P																																										
CRCW1210-P																																										
CRCW1218-P																																										
CRCW2010-P																																										
CRCW2512-P																																										
100																																										
TCR																																										
± 25 ppm/K																																										
± 50 ppm/K																																										
± 100 ppm/K																																										
75R																																										
RESISTANCE VALUE																																										
49K9 = 49.9 kΩ																																										
5R1 = 5.1 Ω																																										
0.5 %																																										
TOLERANCE																																										
± 0.25 %																																										
± 0.5 %																																										
± 1.0 %																																										
ET7																																										
PACKAGING (5)																																										
ET1, ET5																																										
ET6, ET7																																										
EF4, EG1																																										
E20, ET0																																										
E02, E67																																										
E82, E27																																										
e3																																										
LEAD (Pb)-FREE																																										
e3 = Pure tin																																										
Termination finish																																										

Notes

- (4) Preferred way for ordering products is by use of the PART NUMBER
- (5) Please refer to table PACKAGING, see next page

PACKAGING											
MODEL	REEL								BULK		
	TAPE WIDTH	DIAMETER	PITCH	PIECES/ REEL	PACKAGING CODE				PIECES	PACKAGING CODE	
					PART NUMBER		PRODUCT DESC.			PART NUMBER	PRODUCT DESC.
					PAPER	BLISTER	PAPER	BLISTER			
D10/CRCW0402-P	8 mm	180 mm/7"	2 mm	10 000	ED		ET7		50 000	EY	E27
		330 mm/13"	2 mm	50 000	EE		EF4				
D11/CRCW0603-P	8 mm	180 mm/7"	4 mm	5000	EA	EI	ET1	EG1	25 000	EY	E27
		285 mm/11.25"	4 mm	10 000	EB		ET5				
		330 mm/13"	4 mm	20 000	EC	EL	ET6	E20			
D12/CRCW0805-P	8 mm	180 mm/7"	4 mm	5000	EA	EI	ET1	EG1	10 000	EY	E27
		285 mm/11.25"	4 mm	10 000	EB		ET5				
		330 mm/13"	4 mm	20 000	EC	EL	ET6	E20			
D25/CRCW1206-P	8 mm	180 mm/7"	4 mm	5000	EA	EI	ET1	EG1			
		285 mm/11.25"	4 mm	10 000	EB		ET5				
		330 mm/13"	4 mm	20 000	EC	EL	ET6	E20			
CRCW1210-P	12 mm	180 mm/7"	4 mm	5000	EA		ET1				
		285 mm/11.25"	4 mm	10 000	EB		ET5				
		330 mm/13"	4 mm	20 000	EC		ET6				
CRCW1218-P	12 mm	180 mm/7"	4 mm	4000		EK		ET9			
CRCW2010-P	12 mm	180 mm/7"	4 mm	4000		EF		E02			
CRCW2512-P	12 mm	180 mm/7"	8 mm	2000		EG		E67			
			4 mm	4000		EH		E82			

**DIMENSIONS**







SIZE		DIMENSIONS [in millimeters]				
INCH	METRIC	L	W	H	T1	T2
0402	1005	1.0 ± 0.05	0.5 ± 0.05	0.35 ± 0.05	0.25 ± 0.05	0.2 ± 0.1
0603	1608	1.55 <sup>+0.10</sup> <sub>-0.05</sub>	0.85 ± 0.1	0.45 ± 0.05	0.3 ± 0.2	0.3 ± 0.2
0805	2012	2.0 <sup>+0.20</sup> <sub>-0.10</sub>	1.25 ± 0.15	0.45 ± 0.05	0.3 <sup>+0.20</sup> <sub>-0.10</sub>	0.3 ± 0.2
1206	3216	3.2 <sup>+0.10</sup> <sub>-0.20</sub>	1.6 ± 0.15	0.55 ± 0.05	0.45 ± 0.2	0.4 ± 0.2
1210	3225	3.2 ± 0.2	2.5 ± 0.2	0.55 ± 0.05	0.45 ± 0.2	0.4 ± 0.2
1218	3246	3.2 <sup>+0.10</sup> <sub>-0.20</sub>	4.6 ± 0.15	0.55 ± 0.05	0.45 ± 0.2	0.4 ± 0.2
2010	5025	5.0 ± 0.15	2.5 ± 0.15	0.6 ± 0.1	0.6 ± 0.2	0.6 ± 0.2
2512	6332	6.3 ± 0.2	3.15 ± 0.15	0.6 ± 0.1	0.6 ± 0.2	0.6 ± 0.2

SIZE		SOLDER PAD DIMENSIONS [in millimeters]					
		REFLOW SOLDERING			WAVE SOLDERING		
INCH	METRIC	a	b	l	a	b	l
0402	1005	0.4	0.6	0.5			
0603	1608	0.5	0.9	1.0	0.9	0.9	1.0
0805	2012	0.7	1.3	1.2	0.9	1.3	1.3
1206	3216	0.9	1.7	2.0	1.1	1.7	2.3
1210	3225	0.9	2.5	2.0	1.1	2.5	2.2
1218	3246	1.05	4.9	1.9	1.25	4.8	1.9
2010	5025	1.0	2.5	3.9	1.2	2.5	3.9
2512	6332	1.0	3.2	5.2	1.2	3.2	5.2



Lead (Pb)-free Thick Film, Rectangular,  
Precision Chip Resistors

Vishay



<b>TEST PROCEDURES AND REQUIREMENTS</b>		
EN 60115-1		
TEST (clause)	CONDITIONS OF TEST	REQUIREMENTS PERMISSIBLE CHANGE ( $\Delta R/R$ )
		STABILITY CLASS 1 OR BETTER
	Stability for product types: <b>D../CRCW....-P e3</b>	10R to 10M
Resistance (4.5)	-	$\pm 1; \pm 0.5; \pm 0.25$
Temperature coefficient (4.8.4.2)	20/- 55/20 °C and 20/125/20 °C	$\pm 100$ ppm/K; $\pm 50$ ppm/K; $\pm 25$ ppm/K
Overload (4.13)	$U = 2.5 \times (P_{70} \times R)^{1/2}$ $\leq 2 \times U_{max.}$ ; Duration: according the style	$\pm (0.25 \% R + 0.05 \Omega)$
Solderability (4.17.5)	Aging 4 h at 155 °C, dryheat solder bath method; 235 °C; 2 s visual examination	Good tinning ( $\geq 95$ % covered) no visible damage
Resistance to soldering heat (4.18.2)	Solder bath method; (260 $\pm$ 5) °C; (10 $\pm$ 1) s	$\pm (0.25 \% R + 0.05 \Omega)$
Rapid change of temperature (4.19)	30 min at LCT = - 55 °C; 30 min at UCT = 125 °C; 5 cycles	$\pm (0.25 \% R + 0.05 \Omega)$
Damp heat, steady state (4.24)	(40 $\pm$ 2) °C; 56 days; (93 $\pm$ 3) % RH	$\pm (1 \% R + 0.05 \Omega)$
Climatic sequence (4.23)	16 h at UCT = 125 °C; 1 cycle at 55 °C; 2 h at LCT = - 55 °C; 1 h/1 kPa at 15 °C to 35 °C; 5 cycles at 55 °C $U = (P_{70} \times R)^{1/2}$ $U = U_{max.}$ ; whichever is less severe	$\pm (1 \% R + 0.05 \Omega)$
Endurance at 70 °C (4.25.1)	$U = (P_{70} \times R)^{1/2}$ $U = U_{max.}$ ; whichever is less severe 1.5 h ON; 0.5 h OFF; 70 °C; 1000 h	$\pm (1 \% R + 0.05 \Omega)$
Extended endurance (4.25.1.8)	Duration extended to 8000 h	$\pm (2 \% R + 0.1 \Omega)$
Endurance at upper category temperature (4.25.3)	UCT = 125 °C; 1000 h	$\pm (1 \% R + 0.05 \Omega)$

<b>APPLICABLE SPECIFICATIONS</b>	
• EN 60115-1	Generic Specification
• EN 140400	Sectional Specification
• EN 140401-802	Detail Specification
• IEC 60068-2-X	Variety of environmental test procedures
• IEC 60286-3	Packaging of SMD components



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.