



**F E A T U R E S**

**DIRECTLY REPLACES STANDARD INCANDESCENTS**

- LONG LIFE / 100,000 HOURS
- CHOICE OF 8 COLORS
- SOLID STATE, HIGH SHOCK/ VIBRATION RESISTANT
- LOW CURRENT, POWER SAVINGS to 100 - 500% AND MORE
- BUILT-IN CURRENT LIMITING RESISTOR FOR DIRECT APPLICATIONS FOR 2V to 240VAC
- USED IN PILOT LIGHTS, INDUSTRIAL CONTROLS, LIGHTED PUSH BUTTON SWITCHES...

**REPLACES FOLLOWING INCANDESCENTS**

MINIATURE FLANGE: PR20, PR18, PR16, PR15, PR13, PR8, PR7, PR6, PR4, PR3, PR2...

PART NO.: **F 3 1 2 7 C R 6 - 2 8 V / 3 0 - P**

MODEL #	LENS / COLOR / BRIGHT	VOLTS / mAmps Typ	POLARITY
<b>CLUSTERED LED<sub>s</sub></b> T3-1/4(9mm)  <b>FLANGE:</b> F3127 = 7 LEDs F3126 = 6 LEDs	CR7, CR6, CR5, CO5, CY5, CLY5, CG5, CPG5, CB5, CW5  <b>SPECIALS:</b> COPG5=BICOLOR O/PG CRPG5=BICOLOR R/PG	<b>3126:6Vf =NO RES. REQ'D</b> 8V/60, 12V/60, 14V/60 <b>3127:14Vf= NO RES.REQ'D</b> 24V/30, 28V/30, 36V/20, 48V/20, 60V/15, 120VAV/10 Other Voltages / mAmps Available	<b>CENTER CONTACT:</b> P = ANODE (+) N = CATH. (-) P/NR = ANODE/ NO RESISTOR BP = BIPOLAR AC = VAC
<b>MULTICHIP LED<sub>s</sub></b> T3-1/4(9mm)  <b>FLANGE: 6 CHIP</b> F3306, FM326	CR3K, CR7, CR6, CO6, CY6, CLY6, CG6, CPG6, CB6, CW6  <b>SPECIALS:</b> CRPG6 = BICOLOR R/PG COPG6 = BICOLOR O/PG	<b>4Vf,6Vf,12Vf=NO RES. REQ'D</b> 5V/60, 6V/60, 12V/30, 14V/30, 24V/20, 28V/20, 36V/15, 48V/15, 60V/12, 120VAC/8 Other Voltages / mAmps Available	<b>CENTER CONTACT:</b> P = ANODE (+) N = CATH. (-) P/NR = ANODE/ NO RESISTOR BP = BIPOLAR AC = VAC
<b>DUAL CHIP LED</b> T3-1/4(9mm)  <b>FLANGE: F3302, F322</b>	CR3K, CR5, CO5, CY5, CG5,	<b>4Vf =NO RES. REQ'D</b> 5V/30, 6V/30, 12V/30, 14V/30, 24V/30, 28V/20...  Other Voltages / mAmps Available	<b>CENTER CONTACT:</b> P = ANODE (+) N = CATH. (-) P/NR = ANODE/ NO RESISTOR AC = VAC
<b>SINGLE CHIP LED</b> T3-1/4(9mm)  <b>FLANGE: F330, F321</b>	CR5K, CR3K, CR900, CR6, CR5, CO5, CY5, CLY5, CG5, CPG6, CPG5, CB4, CB5	<b>2Vf =NO RES. REQ'D</b> 5V/30, 6V/30, 12V/30, 14V/30, 24V/20, 28V/20...  Other Voltages / mAmps Available	<b>CENTER CONTACT:</b> P = ANODE (+) N = CATH. (-) P/NR = ANODE/ NO RESISTOR AC = VAC
<b>10mm BULB LED</b> 1 CHIP / LOW COST  <b>FLANGE: F300</b>	CR3K, CR6, CR4, CY4, CG4, TR6, TR4, TY4, TG4	<b>2Vf = NO RES. REQ'D</b> 5V/30, 6V/30, 12V/30, 14V/30, 24V/20, 28V/20...  Other Voltages / mAmps Available	<b>CENTER CONTACT:</b> P = ANODE (+) N = CATH. (-) P/NR = ANODE/ NO RESISTOR

**SPECIALS: BICOLORS, BLINKING, INFRAREDS, RIGHT-ANGLE ILLUMINATORS...**

LENS TYPE: C=CLEAR, T=TRANSLUCENT (DIFFUSED),  
 COLOR CODES: R=RED, O=ORANGE, Y=AMBER YELLOW, LY=LIME YELLOW, G=GREEN,  
 PG=PURE GREEN, B=BLUE, W=WHITE (RED/GREEN)

BRIGHTNESS CODES: 900 = 900mcd WIDE RED, 3K = 3Kmcd NARROW RED, 7 = HI ULTRA RED ONLY,  
 6 = ULTRA, 5 = SUPER BRIGHT, 3/4 = HI EFFICIENCY

NOTE: WHEN PLACING ORDERS OR REQUESTING SAMPLES, PLEASE INDICATE INCANDESCENT LAMP NUMBER BEING REPLACED. WHEN SELECTING THE LED COLOR, MATCH EXISTING LENS COLOR TO LED COLOR.

