

LED



T3-1/4(9mm) MIN. BASED LEDs MINIATURE WEDGE

FEATURES

DIRECTLY REPLACES STANDARD INCANDESCENTS

- LONG LIFE / 100,000 HOURS
- CHOICE OF 8 COLORS
- SOLID STATE, HIGH SHOCK/ VIBRATION RESISTANT
- LOW CURRENT, POWER SAVINGS to 100 - 500% AND MORE
- BUILT-IN CURRENT LIMITING RESISTOR FOR DIRECT APPLICATIONS FOR 2V to 240VAC
- USED IN PILOT LIGHTS, INDUSTRIAL CONTROLS, LIGHTED PUSH BUTTON SWITCHES...

REPLACES FOLLOWING INCANDESCENTS

MINIATURE WEDGE: 159, 259, 555, 280, 192, 658, 161, 158, 194, 193, 168, 758, 184, 656, 657, 400, 464, 655...

PART NO.:

W3127CR6-28V/30-

MODEL #	LENS / COLOR / BRIGHT	VOLTS / mAmps Typ	POLARITY
CLUSTERED LED T3-1/4(9mm) WEDGE: W3127 = 7 LEDs W3126 = 6 LEDs	CR7, CR6, CR5, CO5, CY5, CLY5, CG5, CPG5, CB5, CW5 SPECIALS: COPG5=BICOLOR O/PG CRPG5=BICOLOR R/PG	3126:6Vf =NO RES. REQ'D 8V/60, 12V/60, 14V/60 3127:14Vf =NO RES. REQ'D 24V/30, 28V/30, 36V/20, 48V/20, 60V/15, 120VAC/10 Other Voltages / mAmps Available	CENTER CONTACT: BLANK = FOR STD DC TYPE AC = VAC NR = ANODE/ NO RESISTOR
MULTICHIP LED T3-1/4(9mm) WEDGE: 6 CHIP W326	CR3K, CR7, CR6, CO6, CY6, CLY6, CG6, CPG6, CB6, CW6 SPECIALS: CRPG6 = BICOLOR R/PG COPG6 = BICOLOR O/PG	4Vf, 6Vf, 12Vf =NO RES. REQ'D 5V/60, 6V/60, 12V/30, 14V/30, 24V/20, 28V/20, 36V/15, 48V/15, 60V/12, 120VAC/8 Other Voltages / mAmps Available	CENTER CONTACT: BLANK = FOR STD DC TYPE AC = VAC NR = ANODE/ NO RESISTOR BP = BIPOLAR
DUAL CHIP LED T3-1/4(9mm) WEDGE: W322	CR3K, CR5, CO5, CY5, CG5,	4Vf =NO RES. REQ'D 5V/30, 6V/30, 12V/30, 14V/30, 24V/30, 28V/20... Other Voltages / mAmps Available	CENTER CONTACT: BLANK = FOR STD DC TYPE AC = VAC NR = ANODE/ NO RESISTOR
SINGLE CHIP LED T3-1/4(9mm) WEDGE: W321,	CR5K, CR3K, CR900, CR6, CR5, CO5, CY5, CLY5, CG5, CPG6, CPG5, CB4, CB5	2Vf = NO RES. REQ'D 5V/30, 6V/30, 12V/30, 14V/30, 24V/20, 28V/20... Other Voltages / mAmps Available	CENTER CONTACT: BLANK = FOR STD DC TYPE AC = VAC NR = ANODE/ NO RESISTOR
10mm BULB LED 1 CHIP / LOW COST WEDGE: W300	CR3K, CR6, CR4, CY4, CG4, TR6, TR4, TY4, TG4	2Vf =NO RES. REQ'D 5V/30, 6V/30, 12V/30, 14V/30, 24V/20, 28V/20... Other Voltages / mAmps Available	BLANK = FOR STD DC TYPE AC = VAC NR = ANODE/ NO RESISTOR

SPECIALS: BICOLORS, BLINKING , INFRAREDS, RIGHT ANGLE ILLUMINATORS...

LENS TYPE: C=CLEAR, T=TRANSLUCENT (DIFFUSED),

COLOR CODES: R=RED, O=ORANGE, Y=AMBER YELLOW, LY=LIME YELLOW, G=GREEN,

PG=PURE GREEN, B=BLUE, W=WHITE (RED/GREEN)

BRIGHTNESS CODES: 900 = 900mcd WIDE RED, 3K = 3K mcd NARROW RED, 7 = HI ULTRA RED ONLY,

6 = ULTRA, 5 = SUPER BRIGHT, 3/4 = HI EFFICIENCY

NOTE: WHEN PLACING ORDERS OR REQUESTING SAMPLES, PLEASE INDICATE INCANDESCENT LAMP NUMBER BEING REPLACED. WHEN SELECTING THE LED COLOR, MATCH EXISTING LENS COLOR TO LED COLOR.

