

3 Electrical Characteristics

3.1 Absolute Maximum Ratings Over Operating Free-Air Temperature Range (unless otherwise noted)[†]

Supply voltage, V _{DD} (see Note 1)	7	V
Input voltage range, V _I	-0.5	V to V _{DD} + 0.5 V
Analog output short-circuit duration to any power supply or common	unlimited	
Operating free-air temperature range, T _A	0	°C to 70°C
Storage temperature range	-65	°C to 150°C
Junction temperature	175	°C
Case temperature for 10 seconds: PCA and MEP packages	260	°C
Lead temperature 1.6 mm (1/16 inch) from case for 10 seconds	260	°C

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: All voltage values are with respect to GND.

3.2 Recommended Operating Conditions

	MIN	NOM	MAX	UNIT
Supply voltages, AV _{DD} , DV _{DD}	4.75	5	5.25	V
Reference voltage, V _{ref}	1.15	1.235	1.26	V
High-level input voltage, V _{IH}	2.4		V _{DD} +0.5	V
Low-level input voltage, V _{IL}			0.8	V
Output load resistance, R _L		37.5		Ω
FS ADJUST resistor, R _{SET}		523		Ω
XTAL1/XTAL2 crystal frequency		14.31818		MHz
Operating free-air temperature, T _A	0		70	°C

3.3 Electrical Characteristics

PARAMETER		TEST CONDITIONS	MIN	TYPT†	MAX	UNIT
V _{OH}	High-level output voltage	I _{OH} = -800 µA	2.4			V
V _{OL}	Low-level output voltage	D(7-0), RCLK, SENSE, PCLKOUT, MCLK	I _{OL} = 3.2 mA		0.4	V
		H SYNCOUT, V SYNCOUT	I _{OL} = 15 mA		0.4	
		SCLK	I _{OL} = 18 mA		0.4	
I _{IH}	High-level input current	TTL inputs	V _I = 2 V		1	µA
I _{IL}	Low-level input current	TTL inputs	V _I = 0.8 V		-1	µA
I _{DD}	Supply current	TVP3030-175			600	mA
		TVP3030-220			650	
		TVP3030-250			700	
I _{OZ}	High-impedance-state output current				10	µA
C _i	Input capacitance	TTL inputs	f = 1 MHz, V _I = 2 V	4		pF

† All typical values are at V_{DD} = 5 V, T_A = 25°C.

3.4 Operating Characteristics

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
Resolution (each DAC)		8-bit mode		8		bits
		6-bit mode		6		
E_L End-point linearity error (each DAC)		8-bit mode			1	LSB
		6-bit mode			1/4	
E_D Differential linearity error (each DAC)		8-bit mode		1		LSB
		6-bit mode			1/4	
Gray scale error					5%	
Output current (see Note 3)		White level relative to blank	17.69	19.05	20.4	mA
		White level relative to black (7.5 IRE only)	16.74	17.62	18.5	mA
		Black level relative to blank (7.5 IRE only)	0.95	1.44	1.9	mA
		Blank level on IOR, IOB	0	5	50	μ A
		Blank level on IOG (with SYNC enabled)	6.29	7.6	8.96	mA
		Sync level on IOG (with SYNC enabled)	0	5	50	μ A
		One LSB (8/6 high)			69.1	μ A
		One LSB (8/6 low)			276.4	μ A
DAC-to-DAC matching				2%	5%	
DAC-to-DAC crosstalk				-20		dB
Output compliance				-1	1.2	V
Voltage reference output voltage				1.15	1.235	1.26
Output impedance				50		$k\Omega$
Output capacitance				13		pF
Sense voltage reference				300	350	400
Clock and data feedthrough				-20		dB
Glitch area (see Note 4)				50		pV-s
Pipeline delay, VGA port				17		DOTCLK periods
Pipeline delay, pixel port				17		DOTCLK periods
Pixel clock PLL, MCLK PLL	Lock time			5		ms
	Jitter			± 200		ps

- NOTES:
- 3. Test conditions for RS343-A video signals (unless otherwise specified): "Recommended Operating Conditions", using external voltage reference $V_{ref} = 1.235$ V, $R_{SET} = 523 \Omega$. When using the internal voltage reference, R_{SET} may need to be adjusted in order to meet these limits.
 - 4. Glitch area does not include clock and data feedthrough. The -3-dB test bandwidth is twice the clock rate.

3.5 Timing Requirements (see Note 5)

		TVP3030 -175		TVP3030 -220		TVP3030 -250		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
DOTCLK frequency		175		220		250		MHz
Pixel clock PLL	Internal frequency	175		220		250		MHz
	PCLKOUT frequency	110		110		110		MHz
MCLK PLL frequency		100		100		100		MHz
VCO frequency, pixel clock PLL, MCLK PLL, and loop clock PLL		110	220	110	220	110	250	MHz
CLK0 frequency for VGA mode 2		85		85		85		MHz
t _{cyc}	Clock cycle time	TTL	7.1	7.1	7.1	7.1	ns	
t _{d4}	Delay time, RCLK to LCLK (see Note 6)		0.5		0.5		0.5	RCLK periods
t _{su1}	Setup time, RS(3-0) valid before \overline{RD} or $\overline{WR}\downarrow$		10		10		10	ns
t _{h1}	Hold time, RS(3-0) valid after \overline{RD} or $WR\downarrow$		10		10		10	ns
t _{su2}	Setup time, D(7-0) valid before $WR\uparrow$		35		35		35	ns
t _{h2}	Hold time, D(7-0) valid after $WR\uparrow$		0		0		0	ns
t _{su3}	Setup time, VGA(7-0) and $VGAHS$, $VGAVS$, and $VGABL$ valid before CLK0 \uparrow		2		2		2	ns
t _{h3}	Hold time, VGA(7-0) and $VGAHS$, $VGAVS$, and $VGABL$ valid after CLK0 \uparrow		2		2		2	ns
t _{su4}	Setup time, P(127-0), VGA(7-0), and PSEL valid before LCLK \uparrow		2		2		2	ns
t _{h4}	Hold time, P(127-0), VGA(7-0), and PSEL valid after LCLK \uparrow		1		1		1	ns
t _{su5}	Setup time, $SYSHS$, $SYSVS$, and OVS valid before LCLK \uparrow		2		2		2	ns
t _{h5}	Hold time, $SYSHS$, $SYSVS$, and OVS valid after LCLK \uparrow		1		1		1	ns
t _{su6}	Setup time, $SYSBL$ valid before LCLK \uparrow		3		3		3	ns
t _{h6}	Hold time, $SYSBL$ valid after LCLK \uparrow		2		2		2	ns
t _{w1}	Pulse duration, \overline{RD} or \overline{WR} low		50		50		50	ns
t _{w2}	Pulse duration, \overline{RD} or \overline{WR} high		30		30		30	ns
t _{w3}	Pulse duration, clock high	TTL	3		2		2	ns
t _{w4}	Pulse duration, clock low	TTL	3		2		2	ns

- NOTES:
- 5. TTL input signals are 0 to 3 V with less than 3 ns rise/fall time between the 10% and 90% levels unless otherwise specified. For input and output signals, timing reference points are at the 10% and 90% signal levels. Analog output loads are less than 10 pF. D7-D0 output loads are less than 50 pF. All other output loads are less than 50 pF unless otherwise specified.
 - 6. This parameter only applies when SCLK is used as the VRAM shift clock. When SCLK is not used, the delay may be as much as is required by system logic (assuming the loop clock PLL is used to compensate for the system delay).

3.6 Switching Characteristics

PARAMETER	TVP3030-175			TVP3030-220			TVP3030-250			UNIT
	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
SCLK/RCLK frequency (see Note 7)			85			85			85	MHz
t_{en1} Enable time, \overline{RD} low to D(7-0) valid			40			40			40	ns
t_{dis1} Disable time, \overline{RD} high to D(7-0) disabled			17			17			17	ns
t_{v1} Valid time, D(7-0) valid after \overline{RD} high	5			5			5			ns
t_{d1} Delay time, \overline{RD} low to D(7-0) starting to turn on	5			5			5			ns
t_{d2} Delay time, CLK0 to DOTCLK (internal signal) high/low		7			7			7		ns
t_{d3} Delay time, SCLK high/low to RCLK high/low (see Notes 8, 9, and 10)	1	2	4	1	2	4	1	2	4	ns
t_{d6} Analog output settling time (see Note 11)		5			5			4		ns
t_r Analog output rise time (see Note 12)		2			2			2		ns
Analog output skew	0		2	0		2	0		2	ns

- NOTES:
- 7. SCLK can drive an output capacitive load up to 60 pF. The worst-case transition time between the 10% and 90% levels is less than 4 ns (typical 3 ns). RCLK can drive output capacitive loads up to 15 pF, with worst case transition times between 10% and 90% levels less than 4 ns (typical 3 ns).
 - 8. The SCLK delay time to RCLK depends on the load that the signals drive. This parameter is measured with an RCLK load of 15 pF and SCLK load of 60 pF.
 - 9. In SCLK mode, RCLK is delayed from SCLK in such a way that when RCLK is connected to LCLK, the VRAM serial output hold time is used.
 - 10. This parameter applies when SCLK is used.
 - 11. Measured from 50% point of full scale transition to output settling, within ± 1 LSB (settling time does not include clock and data feedthrough).
 - 12. Measured between 10% and 90% of full scale transition.

3.7 Timing Diagrams




Figure 3–1. MPU Interface Timing




Figure 3–2. Video Input/Output Timing