

P-tec Corp.
 2405 Commerce Circle
 Alamosa Co. 81101
 www.p-tec.net

Tel:(800)688-0613
 Tel:(719) 589 3122
 Fax:(719) 589 3592
 sales@p-tec.net



PL16 Series 5mm (T1¾) LED

Features

- *Popular T1 3/4 Lens style with Flange
- *AlGaInP Ultra Bright Red Chip used
- *Narrow Viewing Angle
- *High Intensity
- *Ultra High Light Output
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation	72mW
Reverse Voltage (<100µA).....	5.0V
Max Forward Current	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Dominant Wave Length	Peak Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
PL16D-WCR18	Deep Red	AlInGaP	639	650	20°	1.9	2.4	429.0	800.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

