

6 Amp Glass Passivated Quick Connect Rectifier

Features

- Package suitable for assembly
- Glass passivated junction
- High current capability
- Plastic package has underwriters laboratory flammability classification 94 V-O
- RoHS compliant



Mechanical Data

Case:	Pplastic transfer molded
Terminals:	Plated 0.25" fast on terminals
Polarity:	cathode end indicated by color band
Weight:	3.37 gram

Maximum Ratings & Electrical Characteristics ($T_{Ambient}=25^{\circ}C$ unless noted)

Symbol	Description	GT 605G	GT 61G	GT 62G	GT 64G	GT 66G	GT 68G	GT 610G	Unit	Conditions
V_{RRM}	Max. Recurrent Peak Reverse Voltage	50	100	200	400	600	800	1000	V	
V_{RMS}	Max. RMS Voltage	35	70	140	280	420	560	700	V	
V_{DC}	Max. DC Blocking Voltage	50	100	200	400	600	800	1000	V	
I_{F(AV)}	Max. Average Forward Rectified Current	6.0							A	TA=60°C
		22								TL=60°C
I_{FSM}	Peak Forward Surge Current	400							A	8.3ms single half sine-wave on rated load
V_F	Max. Instantaneous Forward Voltage	1.0							V	I _F at 6.0 A
I_R	Max. DC Reverse Current	10							µA	At rated V _{RRM}
C_J	Typical Junction Capacitance	150							pf	at f=1.0 MHz and V _r = 4.0 volts
R_{θ-JA}	Maximum Thermal Resistance	20							° C/W	
T_J, T_{ST}_G	Operating Junction and Storage Temperature Range	-55 to 150							° C	

6 Amp Glass Passivated Quick Connect Rectifier

GT605G~ GT610G

Typical Characteristics Curves




Fig.1- Forward Current Derating Curve




Fig.2- Max. Non-Repetitive Forward Surge Current




Fig.3- Typical Instantaneous Forward Characteristics





Fig.4- Typical Reverse Characteristics

6 Amp Glass Passivated Quick Connect Rectifier

GT605G~ GT610G

Dimensions in inch (mm)



How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 247-2232 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.

42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

CROSS REGION PLAZA, 899 LINGLING ROAD, SUITE 18C, SHANGHAI, 200030, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931