

M3H & MH Series



8 pin DIP, 5.0 or 3.3 Volt, HCMOS/TTL Clock Oscillator



- 5.0 Volt or 3.3 Volt Versions
- RoHS Compliant Version available
- Low Jitter

Ordering Information

	M3H / MH	1	3	F	A	D	-R	00.0000	MHz
Product Series	M3H = 3.3 Volt MH = 5.0 Volt								
Temperature Range	1: 0°C to +70°C 2: -40°C to +85°C 3: -55°C to +105°C 4: -55°C to +125°C 5: -10°C to +85°C 6: -20°C to +70°C 7: 0°C to +85°C								
Stability	1: ±1000 ppm 2: ±500 ppm 3: ±100 ppm 4: ±50 ppm 5: ±35 ppm 6: ±25 ppm 7: +0/-200 ppm *8: ±20 ppm								
Output Type	F: Fixed T: Tristate								
Symmetry/Logic Compatibility	A: 40/60 HCMOS/TTL B: 45/55 TTL (MH series only) C: 45/55 HCMOS D: 45/55 HCMOS/TTL (MH to 50 MHz only)								
Package/Lead Configurations	D: DIP; Nickel Header G: Gull Wing; Nickel Header								
RoHS Compliance	Blank: non-RoHS compliant part -R: RoHS compliant part								
Frequency (customer specified)									



All dimensions in inches (mm).

Pin Connections

PIN	FUNCTION
1	N/C or Tristate
4	Circuit/Case Ground
5	Output
8	+Vdd

PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
Frequency Range	F	1.5		100	MHz	M3H See Note 1
		1.0		80	MHz	MH
Operating Temperature	T _A	(See Ordering Information)				
Storage Temperature	T _s	-55		+125	°C	
Frequency Stability	ΔF/F	(See Ordering Information)				
Aging						
1st Year			±3		ppm	
Thereafter (per year)			±2		ppm	
Input Voltage	V _{dd}	3.135	3.3	3.465	V	M3H
		4.5	5.0	5.5	V	MH
Input Current (M3H)	I _{dd}			25	mA	1.500 to 50.000 MHz
				35	mA	50.001 to 67.000 MHz
				55	mA	67.001 to 100.000 MHz
Input Current (MH)	I _{dd}			40	mA	1.000 to 40.000 MHz
				60	mA	40.001 to 80.000 MHz
Output Type		HCMOS/TTL				
Load		2 TTL or 15 pF				M3H
		10 TTL or 50 pF				MH See Note 2
Symmetry (Duty Cycle)		(See Ordering Information)				
Logic "1" Level	V _{oh}	90% V _{dd}			V	HCMOS Load
		V _{dd} -0.5			V	TTL Load
Logic "0" Level	V _{ol}			10% V _{dd}	V	HCMOS Load
				0.5	V	TTL Load
Output Current				±4	mA	M3H
				±16	mA	MH
Rise/Fall Time	T _r /T _f			10	ns	See Note 4
Tristate Function		Input Logic "1" or floating; output active Input Logic "0"; output disables to high-Z				
Start up Time			5		ms	
Random Jitter	R _j		5	12	ps RMS	1-Sigma

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.