



NOTES:  
1. FOR USE WITH N17/119-RG174 & N17/113-RG 316 CABLE.

3. FOR CABLING INSTRUCTIONS SEE CP-439.
4. FOR CABLING TRIMMING USE KTJ-B2 & KTD-121.
5. FOR CRIMPING USE DIE SIZE 21.
6. MARK PACKAGE KINGS 875-9-3 XXXX (DATE CODE)

UNLESS OTHERWISE SPECIFIED:  
1. TOLERANCES FRACTIONS & 2 PLACE DECIMALS & ANGLES 30° OR MORE SURFACE FINISHES AS SPECIFIED IN DRAWING UNLESS OTHERWISE SPECIFIED.  
2. PLACE DECIMALS & ANGLES 30° OR MORE SURFACE FINISHES AS SPECIFIED IN DRAWING UNLESS OTHERWISE SPECIFIED.  
3. ALL DIMENSIONS PRIOR TO PLATING.  
4. SURFACE FINISHES AS SPECIFIED IN DRAWING UNLESS OTHERWISE SPECIFIED.  
5. ALL DIMENSIONS PRIOR TO PLATING.

S-D

S-D

(SHEET 1 OF 2)  
M39012/55-3112

REVISIONS	CHANGES
0	RESTRICTED USAGE ER 24354 M.A. 15 MAR 83
1	CN 24465 E RESTRICTED USAGE M.A. 15 APR 83
2	CN 24710 E RESTRICTION REMOVED M.A. 21 JUN 83
3	CN 24703 A GJG 26 OCT 83
4	CN 26034 C AT 13 APR 84 CN 29594 D AJ 9 FEB 88
5	CN 32308 A LNM 21 JUN 90

SCALE	5:1
USED ON	875-9-3
REV	
FINISH	
MATL	KER 10004
SPEC	

5MA PLUG	
DATE	DATE
BY	BY
KINGS ELECTRONICS	
M39012/55-3112	

