



| | |
|----------|---------|
| orange 1 | green 2 |
| white | white |
| blue 3 | brown 4 |
| white | white |

Material:

- Plug: YUS-06 8P8C 50μ"
- Conductor:
 - Wire: Cat.6 PIMF STR 26AWG
 - Bare Copper 26AWG 7/0.16±0.015MM
- Insulator:
 - Thickness Min. at any point: 0.2MM
 - Thickness Max. Avg.: 0.35MM
 - Diameter: 1.05±0.06MM
- Jacket PVC:
 - Thickness Min. at any point: 0.50MM
 - Thickness Max. Avg.: 0.60MM
 - Diameter: 6.1±0.02MM

| PA/R | PINOUT | | |
|------|-----------|------|-----------|
| | P1(T568B) | WIRE | P2(T568B) |
| 1 | 1 | WHT | 1 |
| | 2 | ORG | 2 |
| 2 | 3 | WHT | 3 |
| | 6 | GRN | 6 |
| 3 | 4 | BLU | 4 |
| | 5 | WHT | 5 |
| 4 | 7 | WHT | 7 |
| | 8 | PPN | 8 |

Ⓜ = Assmann logo



ITEM NO.
A-MCSSP60200/B-R
 TITLE
 Cat.6 SFTP Patch Cable - 8P8C 50μ", Blue, 20 Meters

ASSMANN
 Electronics, Inc.
 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
 Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
 ©Copyright 2010 by Assmann Electronic Components
 All International Rights Reserved