



- NOTES:
- FOR USE WITH BOEING BMS13-65 OG & ADAMS RUSSELL FC20Z CABLE.
 - FOR CABLING INSTRUCTIONS SEE 3-546-1.
 - FOR CRIMPING USE DIE KTH-2216.
 - INTERFACE PER MIL-STD-348, FIG. 301-1.
 - CENTER CONTACT (1-569-35MA9) SUPPLIED UNASSEMBLED.
 - MARK PACKAGE: KINGS 755-93-9 (DATE CODE)
 - MATERIALS:
 - INSULATOR: TEFLON, ASTM D1710
 - K-GRIP SLEEVE: COM. BRONZE, ASTM B135
 - GASKET: SILICONE RUBBER, A-A-59588
 - OUTER CONTACT } BER. COPPER, ASTM B196
 - SPRING WASHER } BER. COPPER, ASTM B196
 - ALL OTHER METAL PARTS: BRASS, ASTM B16
 - FINISHES:
 - CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM B488 OVER
 - .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
 - SPRING WASHER: .00020 MIN SILVER PLATE PER ASTM B700 OVER
 - .00020 MIN COPPER PER ASTM B734 (RoHS)
 - ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290
 - OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
 - ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE: 50 OHMS
 - WORKING VOLTAGE: 500 VRMS
 - FREQUENCY RANGE: DC TO 4 GHZ.
 - WEIGHT: 10.2 GRAMS

755-93-9

REVISIONS	
ISSUE	CHANGES
0	ER 35914 MJB 12/01/94
B	REVISED PER DMF304 & ER35722 KPL 11/04/11
CUSTOMER SALES DRAWING	
<small>THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.</small>	
SCALE	4:1
APPROX SURFACE AREA	
WAS:	E-18628
CAGE CODE:	91836
REF:	BOEING
PLUG, BNC	
DRAWN KH	DATE 03/15/94
DESIGN JT	DATE 03/16/94
APPR. CT	DATE 12/01/94
 <small>Winchester Electronics Corporation 82 Barnes Industrial Road North Wallingford, Connecticut 06492</small>	
755-93-9	