



October 2006



FDFC2P100

Integrated P-Channel PowerTrench® MOSFET and Schottky Diode

-20V, -3A, 150mΩ

Features

- Max $r_{DS(on)}$ = 150mΩ at $V_{GS} = -4.5V$, $I_D = -3.0A$
- Max $r_{DS(on)}$ = 200mΩ at $V_{GS} = -2.5V$, $I_D = -2.2A$
- Low Gate Charge (3.4nC typ)
- Compact industry standard SuperSOT™-6 package

Schottky:



- $V_F < 0.45 V$ at $I_F = 1A$
- RoHS Compliant



General Description

The FDFC2P100 combine the exceptional performance of Fairchild's PowerTrench MOSFET technology with a very low forward voltage drop Schottky barrier rectifier in an SSOT-6 package.

This device is designed specifically as a single package solution for DC to DC converters. It features a fast switching, low gate charge MOSFET with very low on-state resistance. Significant improvement of Thermal Characteristics and Power Dissipation via replacement of independently connected Schottky with internal connection of Schottky Diode Cathode pn to P-Channel PowerTrench MosFET Drain pin.



MOSFET Maximum Ratings $T_A = 25^\circ C$ unless otherwise noted

Symbol	Parameter	Ratings	Units
V_{DS}	Drain to Source Voltage	-20	V
V_{GS}	Gate to Source Voltage	± 12	V
I_D	Drain Current -Continuous (Note 1a)	-3	A
	-Pulsed	-6	
P_D	Power Dissipation (Note 1a) (Note 1b)	1.5 0.8	W
V_{RRM}	Schottky Repetitive Peak Reverse Voltage	20	V
I_O	Schottky Average Forward Current (Note 1a)	1	A
T_J, T_{STG}	Operating and Storage Junction Temperature Range	-55 to +150	°C

Thermal Characteristics

$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1a)	87	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1b)	166	

Package Marking and Ordering Information

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
.100	FDFC2P100	SSOT-6	7"	8mm	3000units

Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

Off Characteristics

BV_{DSS}	Drain to Source Breakdown Voltage	$I_D = -250\mu\text{A}, V_{GS} = 0\text{V}$	-20			V
$\frac{\Delta \text{BV}_{\text{DSS}}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	$I_D = -250\mu\text{A}$, referenced to 25°C		-12		$\text{mV}/^\circ\text{C}$
I_{DSS}	Zero Gate Voltage Drain Current	$V_{GS} = 0\text{V}, V_{DS} = -16\text{V}$			-1	μA
I_{GSS}	Gate to Source Leakage Current	$V_{GS} = \pm 12\text{V}, V_{DS} = 0\text{V}$			± 100	μA

On Characteristics

$V_{GS(\text{th})}$	Gate to Source Threshold Voltage	$V_{GS} = V_{DS}, I_D = -250\mu\text{A}$	-0.6	-0.9	-1.5	V
$\frac{\Delta V_{GS(\text{th})}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	$I_D = -250\mu\text{A}$, referenced to 25°C		3		$\text{mV}/^\circ\text{C}$
$r_{DS(\text{on})}$	Drain to Source On-Resistance	$V_{GS} = -4.5\text{V}, I_D = -3.0\text{A}$		95	150	$\text{m}\Omega$
		$V_{GS} = -2.5\text{V}, I_D = -2.2\text{A}$		150	200	
		$V_{GS} = -4.5\text{V}, I_D = -3.0\text{A}, T_J = 125^\circ\text{C}$		130	252	
g_{FS}	Forward Transconductance	$V_{DS} = -5\text{V}, I_D = -3.0\text{A}$		5.4		S

Dynamic Characteristics

C_{iss}	Input Capacitance	$V_{DS} = -10\text{V}, V_{GS} = 0\text{V}, f = 1\text{MHz}$		335	445	pF
C_{oss}	Output Capacitance			80	105	pF
C_{rss}	Reverse Transfer Capacitance			40	60	pF
R_g	Gate Resistance	f = 1MHz		6		Ω

Switching Characteristics

$t_{d(on)}$	Turn-On Delay Time	$V_{DD} = -10\text{V}, I_D = -3.0\text{A}$ $V_{GS} = -4.5\text{V}, R_{\text{GEN}} = 6\Omega$		9	16	ns
t_r	Rise Time			11	20	ns
$t_{d(off)}$	Turn-Off Delay Time			12	22	ns
t_f	Fall Time			4	8	ns
$Q_{g(\text{TOT})}$	Total Gate Charge at -10V	$V_{GS} = 0\text{V to } -10\text{V}$ $V_{DD} = -4.5\text{V}$ $I_D = -3.0\text{A}$		3.4	4.7	nC
Q_{gs}	Gate to Source Gate Charge			0.9		nC
Q_{gd}	Gate to Drain "Miller" Charge			1.0		nC

Drain-Source Diode Characteristics

I_S	Maximum Continuous Drain to Source Diode forward Current				-1.2	A
V_{SD}	Source to Drain Diode Forward Voltage	$V_{GS} = 0\text{V}, I_S = -1.2\text{A}$ (Note 2)		-0.8	-1.2	V
t_{rr}	Reverse Recovery Time	$I_F = -3.0\text{A}, di/dt = 100\text{A}/\mu\text{s}$		17		ns
Q_{rr}	Reverse Recovery Charge			5		nC


Schottky Diode Characteristics

I_R	Reverse Leakage	$V_R = 20\text{V}$	$T_J = 25^\circ\text{C}$		26	400	μA
			$T_J = 100^\circ\text{C}$		2.7	20	mA
		$V_R = 10\text{V}$	$T_J = 25^\circ\text{C}$		23	200	μA
			$T_J = 100^\circ\text{C}$		2.5	10	mA
V_F	Forward Voltage	$I_F = 500\text{mA}$	$T_J = 25^\circ\text{C}$		0.31	0.4	V
			$T_J = 100^\circ\text{C}$		0.24	0.35	
		$I_F = 1\text{A}$	$T_J = 25^\circ\text{C}$		0.37	0.45	
			$T_J = 100^\circ\text{C}$		0.3	0.42	


FDFC2P100 Integrated P-Channel PowerTrench® MOSFET and Schottky Diode

Notes:

1: $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.



a) 87°C/W when
mounted on a 1in²
pad of 2 oz copper



b) 166°C/W when
mounted on a
minimum pad

2: Pulse Test: Pulse Width <300 ms, Duty Cycle < 2.0%

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted




Figure 1. On Region Characteristics




Figure 2. Normalized On-Resistance vs Drain Current and Gate Voltage




Figure 3. Normalized On-Resistance vs Junction Temperature




Figure 4. On-Resistance vs Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs Source Current

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs Drain to Source Voltage




Figure 9. Schottky Diode Forward Voltage




Figure 10. Schottky Diode Reverse Current




Figure 11. Transient Thermal Response Curve



FAIRCHILD SEMICONDUCTOR TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FACT Quiet Series™	OCX™	SILENT SWITCHER®	UniFET™
ActiveArray™	GlobalOptoisolator™	OCXPro™	SMART START™	UltraFET®
Bottomless™	GTO™	OPTOLOGIC®	SPM™	VCX™
Build it Now™	HiSeC™	OPTOPLANAR™	Stealth™	Wire™
CoolFET™	I ² C™	PACMAN™	SuperFET™	
CROSSVOLT™	i-Lo™	POP™	SuperSOT™-3	
DOME™	ImpliedDisconnect™	Power247™	SuperSOT™-6	
EcoSPARK™	IntelliMAX™	PowerEdge™	SuperSOT™-8	
E ² CMOS™	ISOPLANAR™	PowerSaver™	SyncFET™	
EnSigna™	LittleFET™	PowerTrench®	TCM™	
FACT®	MICROCOUPLER™	QFET®	TinyBoost™	
FAST®	MicroFET™	QS™	TinyBuck™	
FASTR™	MicroPak™	QT Optoelectronics™	TinyPWM™	
FPS™	MICROWIRE™	Quiet Series™	TinyPower™	
FRFET™	MSX™	RapidConfigure™	TinyLogic®	
	MSXPro™	RapidConnect™	TINYOPTO™	
Across the board. Around the world.™		µSerDes™	TruTranslation™	
The Power Franchise®		ScalarPump™	UHC®	
Programmable Active Droop™				

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.