



Banana Plugs and Jacks


Pomona®

STANDARD BANANA PLUGS/JACKS



All dimensions in inches unless otherwise noted.

DO-IT-YOURSELF SOLDERLESS STACKUP BANANA PLUG



Internal set screw holds wire firmly.
 Accepts standard banana plug, fits standard (.166 dia.) banana jack.
MATERIAL: Banana Plug/Jack: Brass; Spring: Heat Treated Beryllium Copper
RATING: 5000 VDC, 15 Amps, +50°C (+122°F) Max. (Model 5230, +150°C (+302°F) Max.)
 Accepts 18-22 AWG wire.

DO-IT-YOURSELF SOLDERLESS STACKUP BANANA PLUG WITH SAFETY SHIELD



Internal set screw holds wire firmly.
 Safety collar insulates exposed wire leads.
 Accepts standard banana plug and fits (.166 dia.) banana jack.
MATERIAL: Banana Plug/Jack: Brass; Spring: Heat Treated Beryllium Copper
RATING: 5000 VDC, 15 Amps, +50°C (+122°F) Max. (Model 4899, +150°C (+302°F) Max.)
 Accepts 18-22 AWG wire.

Pomona ACCESS	Model	Plating	Insulation	Std. Colors	PRICE
90269	1325-*	Nickel	ABS	-0 Black, -1 Brown, -2 Red, -3 Orange, -4 Yellow, -5 Green, -6 Blue, -7 Violet, -8 Gray, -9 White.	1.25 ea. Sold in pkgs of 10
	5406	Gold	ABS	-0 Black, -2 Red	2.50
	5230	Nickel	Polyphenylene Sulfide	-0 Black, -6 Blue	1.65 ea. Sold in pkgs of 10
	6546	Nickel	ABS	Pkg. of 1 ea. of all 10 colors	12.50/pkg

Pomona ACCESS	Model	Plating	Insulation	Std. Colors	PRICE
90300	1825-*	Nickel	ABS	-0 Black, -1 Brown, -2 Red, -3 Orange, -4 Yellow, -5 Green, -6 Blue, -7 Violet, -8 Gray, -9 White.	1.25 ea. Sold in pkgs of 10
	4897	Gold	ABS	-0 Black, -2 Red	2.50
	4899	Nickel	Polyphenylene Sulfide	-0 Black, -6 Blue	1.60 ea. Sold in pkgs of 10
	6545	Nickel	ABS	Pkg of 1 ea. of all 10 colors	12.50 /pkg

DO-IT-YOURSELF IN-LINE SHEATHED BANANA PLUG & JACK



Pomona ACCESS	Model	PRICE
90835	6383-*	2.35
	6383-02	4.70
90836	6384-*	2.35
	6384-02	4.70

Safety-rated plugs and jacks for use with any wire from 22 to 18 AWG with flexible insulation
 Assemble with common hand-tools
 Plugs fit most DMM jacks and DMM test leads to make up your own banana plug or jack test lead or jumper.
 See mating panel jacks (6387 & 6388 on p. 87).
MATERIAL: Nickel-plated brass and Beryllium Copper
RATING: CAT II 300V, 15A
 *STD COLORS: -0 black, -2 red, -02 black & red (2 per pkg)

INSULATED BANANA PLUG WITH FLEXIBLE BOOT



Ideal for making patch cords or field repairs. Snap-on flexible PVC boot allows wire to be crimped or soldered to banana plug.
 Fits standard (.166 dia.) banana jack.
MATERIAL: Banana Plug Body: Brass; Spring: Beryllium Copper; Finish: Nickel Plating
RATING: (Independent of wire) 5000 VDC, 15 Amps, +50°C (+122°F) Max.¹
 *STD COLORS: -0 black, -2 red.
¹Hands-free testing in controlled voltage environments.

Pomona ACCESS	Model	Accepts wire AWG	PRICE
90625	5169-*	22, 20, 18	2.15
	5170-*	16, 14	2.15

INSULATED BANANA JACK WITH FLEXIBLE BOOT



Ideal for making patch cords or field repairs. Snap-on flexible PVC boot allows wire to be crimped or soldered to jack.
MATERIAL: Nickel Plated Brass
RATING: (Independent of wire) 5000 VDC, 15 Amps, +50°C (+122°F) Max.¹
 *STD COLORS: -0 black, -2 red.
¹Hands-free testing in controlled voltage environments.

Pomona ACCESS	Model	Accepts wire AWG	PRICE
90624	5167-*	22, 20, 18	2.10
	5168-*	16, 14	2.10


DO-IT-YOURSELF IN-LINE SHEATHED BANANA PLUG/BANANA JACK



These plugs and jacks are designed to fit together and provide protection from accidental shorting.
MATERIAL: Banana Plug/Jack: Brass; Spring: Beryllium Copper; Insulation: Nylon
RATING: 30V AC/DC, 15 Amps, +80°C (+176°F) Max.
 *STD COLORS: -0 black, -2 red.

Pomona ACCESS	Model	Accepts wire AWG	Wire Access Hole	Description	PRICE
90236	4933-*	22, 20, 18	.159" Dia.	Plug	3.10
	4986-*	16, 14	.200" Dia.	Plug	3.10
	4934-*	22, 20, 18	.159" Dia.	Jack	3.20
	4987-*	16, 14	.200" Dia.	Jack	3.20

DO-IT-YOURSELF RETRACTABLE SHEATH BANANA PLUG



Do-It-Yourself Retractable Sheath Banana Plugs provide fast simple assembly and reliable performance.
 CE rated 300V CAT II, 150V CAT III
¹RATING: 1000 VRMS, 20 Amps, ≤ 2 mΩ.
 Accepts 18-22 AWG wire.
¹Hands free testing in controlled voltage environments.

Pomona ACCESS	Model	Color	PRICE
90260	122505A	Black	3.80
	122506A	Red	3.80