


# Radial Leaded PTC Resettable Fuse



## Specifications:

Lead Material	: Tin plated copper
Soldering Characteristic	: MIL-DTD-202, Method 208E
Insulating Coating	: Flame retardant epoxy
Operating Current	: 100mA to 3.75A
Max. Voltage	: Up to 90V
Temperature Range	: -40°C to 85°C
Applications	: Telecom and wide variety of electronic equipment
Product features	: Low hold current, Solid state, Radial leaded product ideal for up to 90V
Agency Recognition	: UL File E345437

## Electrical Characteristics (23°C)

Part Number	Hold Current I <sub>H</sub> , A	Trip Current I <sub>T</sub> , A	Max. Time to Trip at 5 × I <sub>H</sub>	Max. Current I <sub>MAX</sub> , A	Rated Voltage V <sub>MAX</sub> , V DC	Typical Power Pd, W	Resistance	
							R <sub>MIN</sub> Ω	R <sub>1MAX</sub> Ω
MC36184	0.1	0.2	4	40	72/90	0.38	2.5	7.5
MC36185	0.15	0.35	10			0.7	2.4	7
MC36186	0.17	0.34	3			0.48	2	8
MC33171	0.2	0.4	2.2			0.41	1.83	4.4
MC33172	0.25	0.5	2.5			0.45	1.25	3
MC33173	0.3	0.6	3			0.49	0.88	2.1
MC36190	0.35	0.75	10			1.3	0.7	2.5
MC33174	0.4	0.8	3.8			0.56	0.55	1.29
MC33175	0.5	1	4			0.77	0.5	1.17
MC36193	0.55	1.2	10			1.5	0.4	1.5
MC33176	0.65	1.3	5.3			0.88	0.31	0.72
MC33177	0.75	1.5	6.3			0.92	0.25	0.6
MC33178	0.9	1.8	7.2			0.99	0.2	0.47
MC33179	1.1	2.2	8.2			1.5	0.15	0.38
MC33180	1.35	2.7	9.6			1.7	0.12	0.3
MC33181	1.6	3.2	11.4			1.9	0.09	0.22
MC33182	1.85	3.7	12.6			2.1	0.08	0.19
MC33183	2.5	5	15.6			2.5	0.05	0.13
MC33184	3	6	19.8			2.8	0.04	0.1
MC33185	3.75	7.5	24			3.2	0.03	0.08

I<sub>H</sub> = Hold current-maximum current at which the device will not trip at 23°C still air  
 I<sub>T</sub> = Trip current-minimum current at which the device will always trip at 23°C still air  
 V<sub>MAX</sub> = Maximum voltage device can withstand without damage at its rated current  
 I<sub>MAX</sub> = Maximum fault current device can withstand without damage at rated voltage (V MAX)  
 Pd = Typical power dissipated from device when in tripped state in 23°C still air environment  
 R<sub>MIN</sub> = Minimum device resistance at 23°C  
 R<sub>1MAX</sub> = Maximum device resistance at 23°C, 1 hour after tripping


[www.element14.com](http://www.element14.com)  
[www.farnell.com](http://www.farnell.com)  
[www.newark.com](http://www.newark.com)




# Radial Leaded PTC Resettable Fuse



## Dimensions



Lead Size : 24AWG  
ø0.51mm Diameter



Lead Size : 20AWG  
ø0.81mm Diameter

Part Number	A Max.	B Max.	C Typical	D Min.	E Max.	F Typical	Drawing Option
MC36184	7.4	12.7	5.1	7.6	3.1	1.1	Option 1
MC36185							
MC36186							
MC33171							
MC33172							
MC33173							
MC36190							
MC33174	7.6	13.5	10.2	7.6	3.1	1.4	Option 2
MC33175	7.9	13.7					
MC36193	9.7	14					
MC33176	9.7	14.5					
MC33177	10.4	15.2					
MC33178	11.7	15.8					
MC33179	13	18					
MC33180	14.5	19.6					
MC33181	16.3	21.3					
MC33182	17.8	22.9					
MC33183	21.3	26.4	10.2	7.6	3.1	1.4	Option 2
MC33184	24.9	30					
MC33185	28.5	33.5					

Dimensions : Millimetres

## Thermal Derating Curve

