

Engineering Development Model

Voltage Controlled Oscillator

ROS-ED10353/1

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE : CK605

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Typ.	Max.	Units
Frequency	1640		1953	MHz
Tuning Voltage	0.5		16	V
Power Output		+9		dBm
Phase Noise	at 1 kHz offset	-80		dBc/Hz
	at 10 KHz offset	-103		dBc/Hz
	at 100 KHz offset	-123		dBc/Hz
	at 1000 kHz offset	-143		dBc/Hz
Pulling at 12 dB _r PK-PK all phases		8		MHz
Pushing at V _{cc} =5V±0.25V		0.5		MHz/V
Tuning Sensitivity		20 - 33		MHz/V
Harmonic Suppression		-22		dBc
3 dB Modulation Bandwidth		12000		kHz
Supply Voltage		10		V
Supply Current			30	mA

MAXIMUM RATINGS	
Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Supply Voltage (V _{cc})	+12V
Absolute Tuning Voltage (V _{tune})	+18V

PIN CONNECTIONS	
RF OUT	10
VCC	14
V-TUNE	2
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16

