




Surface Mount TRANSZORB[®] Transient Voltage Suppressors


Stand-off Voltage 5.0 to 188V
Peak Pulse Power 1500W

DO-214AB
(SMC J-Bend)



Extended Voltage Range

Mounting Pad Layout



Features

- Underwriters Laboratory Recognition under UL standard for safety 497B: Isolated Loop Circuit Protection
- Low profile package with built-in strain relief for surface mounted applications
- Glass passivated junction
- Low incremental surge resistance, excellent clamping capability
- 1500W peak pulse power capability with a 10/1000 μ s waveform, repetition rate (duty cycle): 0.01%
- Very fast response time
- High temperature soldering guaranteed: 250°C/10 seconds at terminals

Mechanical Data

- Case:** JEDEC DO-214AB molded plastic over passivated junction
- Terminals:** Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity:** For unidirectional types the band denotes the cathode, which is positive with respect to the anode under normal TVS operation
- Weight:** 0.007 oz., 0.21 g
- Flammability:** Epoxy is rated UL 94V-0

Devices for Bidirectional Applications

For bi-directional devices, use suffix C or CA (e.g. SMCJ10C, SMCJ10CA). Electrical characteristics apply in both directions.

Maximum Ratings & Thermal Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	Value	Unit
Peak pulse power dissipation with a 10/1000 μ s waveform ⁽¹⁾⁽²⁾	PPPM	Minimum 1500	W
Peak pulse current with a 10/1000 μ s waveform ⁽¹⁾	IPPM	See Next Table	A
Peak forward surge current 8.3ms single half sine-wave ⁽²⁾ uni-directional only	IFSM	200	A
Typical thermal resistance, junction to ambient ⁽³⁾	R _{θJA}	75	°C/W
Typical thermal resistance, junction to lead	R _{θJL}	15	°C/W
Operating junction and storage temperature range	T _J , T _{STG}	-55 to +150	°C

Notes: (1) Non-repetitive current pulse, per Fig.3 and derated above T_A = 25°C per Fig. 2

(2) Mounted on 0.31 x 0.31" (8.0 x 8.0mm) copper pads to each terminal

(3) Mounted on minimum recommended pad layout

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified. $V_F = 3.5V$ at $I_F = 100A$ (uni-directional only)

Device Type Modified "J" Bend Lead	Device Marking Code		Breakdown Voltage $V_{(BR)}$ at $I_T^{(1)}$ (V)		Test Current I_T (mA)	Stand-off Voltage V_{WM} (V)	Maximum Reverse Leakage at V_{WM} I_D (μA) ⁽³⁾	Maximum Peak Pulse Surge Current IPPM (A) ⁽²⁾	Maximum Clamping Voltage at IPPM V_C (V)
	UNI	BI	Min	Max					
+SMCJ5.0	GDD	GDD	6.40	7.82	10.0	5.0	1000	156.3	9.6
+SMCJ5.0A ⁽⁵⁾	GDE	GDE	6.40	7.07	10.0	5.0	1000	163.0	9.2
+SMCJ6.0	GDF	GDF	6.67	8.15	10.0	6.0	1000	131.6	11.4
+SMCJ6.0A	GDG	GDG	6.67	7.37	10.0	6.0	1000	145.6	10.3
+SMCJ6.5	GDH	BDH	7.22	8.82	10.0	6.5	500	122.0	12.3
+SMCJ6.5A	GDK	BDK	7.22	7.98	10.0	6.5	500	133.9	11.2
+SMCJ7.0	GDL	GDL	7.78	9.51	10.0	7.0	200	112.8	13.3
+SMCJ7.0A	GDM	GDM	7.78	8.60	10.0	7.0	200	125.0	12.0
+SMCJ7.5	GDN	BDN	8.33	10.2	1.0	7.5	100	104.9	14.3
+SMCJ7.5A	GDP	BDP	8.33	9.21	1.0	7.5	100	116.3	12.9
+SMCJ8.0	GDQ	BDG	8.89	10.9	1.0	8.0	50	100.0	15.0
+SMCJ8.0A	GDR	BDR	8.89	9.83	1.0	8.0	50	110.3	13.6
+SMCJ8.5	GDS	BDS	9.44	11.5	1.0	8.5	20	94.3	15.9
+SMCJ8.5A	GDT	BDT	9.44	10.4	1.0	8.5	20	104.2	14.4
+SMCJ9.0	GDU	BDU	10.0	12.2	1.0	9.0	10	88.8	16.9
+SMCJ9.0A	GDV	BDV	10.0	11.1	1.0	9.0	10	97.4	15.4
+SMCJ10	GDW	BDW	11.1	13.6	1.0	10	5.0	79.8	18.8
+SMCJ10A	GDX	BDX	11.1	12.3	1.0	10	5.0	88.2	17.0
+SMCJ11	GDY	GDY	12.2	14.9	1.0	11	5.0	74.6	20.1
+SMCJ11A	GDZ	GDZ	12.2	13.5	1.0	11	5.0	82.4	18.2
+SMCJ12	GED	BED	13.3	16.3	1.0	12	5.0	68.2	22.0
+SMCJ12A	GEE	BEE	13.3	14.7	1.0	12	5.0	75.4	19.9
+SMCJ13	GEF	GEF	14.4	17.6	1.0	13	1.0	63.0	23.8
+SMCJ13A	GEG	GEG	14.4	15.9	1.0	13	1.0	69.8	21.5
+SMCJ14	GEH	BEH	15.6	19.1	1.0	14	1.0	58.1	25.8
+SMCJ14A	GEK	BEK	15.6	17.2	1.0	14	1.0	64.7	23.2
+SMCJ15	GEL	BEL	16.7	20.4	1.0	15	1.0	55.8	26.9
+SMCJ15A	GEM	BEM	16.7	18.5	1.0	15	1.0	61.5	24.4
+SMCJ16	GEN	GEN	17.8	21.8	1.0	16	1.0	52.1	28.8
+SMCJ16A	GEP	GEP	17.8	19.7	1.0	16	1.0	57.7	26.0
+SMCJ17	GEQ	GEQ	18.9	23.1	1.0	17	1.0	49.2	30.5
+SMCJ17A	GER	GER	18.9	20.9	1.0	17	1.0	54.3	27.6
+SMCJ18	GES	BES	20.0	24.4	1.0	18	1.0	46.6	32.2
+SMCJ18A	GET	BET	20.0	22.1	1.0	18	1.0	51.4	29.2
+SMCJ20	GEU	BEU	22.2	27.1	1.0	20	1.0	41.9	35.8
+SMCJ20A	GEV	BEV	22.2	24.5	1.0	20	1.0	46.3	32.4
+SMCJ22	GEW	BEW	24.4	29.8	1.0	22	1.0	38.1	39.4
+SMCJ22A	GEX	BEX	24.4	26.9	1.0	22	1.0	42.3	35.5
+SMCJ24	GEY	BEY	26.7	32.6	1.0	24	1.0	34.9	43.0
+SMCJ24A	GEZ	BEZ	26.7	29.5	1.0	24	1.0	38.6	38.9
+SMCJ26	GFD	BFD	28.9	35.3	1.0	26	1.0	32.2	46.6
+SMCJ26A	GFE	BFE	28.9	31.9	1.0	26	1.0	35.6	42.1
+SMCJ28	GFF	BFF	31.1	38.0	1.0	28	1.0	30.0	50.0
+SMCJ28A	GFG	BFG	31.1	34.4	1.0	28	1.0	33.0	45.4
+SMCJ30	GFH	BFH	33.3	40.7	1.0	30	1.0	28.0	53.5
+SMCJ30A	GFK	BFK	33.3	36.8	1.0	30	1.0	31.0	48.4

Notes: (1) Pulse test: $t_p \leq 50ms$

(2) Surge current waveform per Fig. 3 and derate per Fig. 2

(3) For bi-directional types having V_{WM} of 10 Volts and less, the I_D limit is doubled

(4) All terms and symbols are consistent with ANSI/IEEE C62.35

(5) For the bi-directional SMCJ/SMCJ5.0CA, the maximum $V_{(BR)}$ is 7.25V

+ Underwriters Laboratory Recognition for the classification of protectors (QVQG2) under the UL standard for safety 497B and file number E136766 for both uni-directional and bi-directional devices



Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. $V_F = 3.5V$ at $I_F = 100A$ (uni-directional only)

Device Type Modified "J" Bend Lead	Device Marking Code		Breakdown Voltage $V_{(BR)}$ at $I_T^{(1)}$ (V)		Test Current I_T (mA)	Stand-off Voltage V_{WM} (V)	Maximum Reverse Leakage at V_{WM} I_D (μA) ⁽³⁾	Maximum Peak Pulse Surge Current I_{PPM} (A) ⁽²⁾	Maximum Clamping Voltage at I_{PPM} V_C (V)
	UNI	BI	Min	Max					
+SMCJ33	GFL	BFL	36.7	44.9	1.0	33	1.0	25.4	59.0
+SMCJ33A	GFM	BFM	36.7	40.6	1.0	33	1.0	28.1	53.3
+SMCJ36	GFN	BFN	40.0	48.9	1.0	36	1.0	23.3	64.3
+SMCJ36A	GFP	BFP	40.0	44.2	1.0	36	1.0	25.8	58.1
+SMCJ40	GFQ	BFQ	44.4	54.3	1.0	40	1.0	21.0	71.4
+SMCJ40A	GFR	BFR	44.4	49.1	1.0	40	1.0	23.3	64.5
+SMCJ43	GFS	BFS	47.8	58.4	1.0	43	1.0	19.6	76.7
+SMCJ43A	GFT	BFT	47.8	52.8	1.0	43	1.0	21.6	69.4
+SMCJ45	GFU	GFU	50.0	61.1	1.0	45	1.0	18.7	80.3
+SMCJ45A	GFV	GFV	50.0	55.3	1.0	45	1.0	20.6	72.7
+SMCJ48	GFW	GFW	53.3	65.1	1.0	48	1.0	17.5	85.5
+SMCJ48A	GFX	GFX	53.3	58.9	1.0	48	1.0	19.4	77.4
+SMCJ51	GFY	GFY	56.7	69.3	1.0	51	1.0	16.5	91.1
+SMCJ51A	GFZ	GFZ	56.7	62.7	1.0	51	1.0	18.2	82.4
+SMCJ54	GGD	GGD	60.0	73.3	1.0	54	1.0	15.6	96.3
+SMCJ54A	GGE	GGE	60.0	66.3	1.0	54	1.0	17.2	87.1
+SMCJ58	GGF	GGF	64.4	78.7	1.0	58	1.0	14.6	103
+SMCJ58A	GGG	GGG	64.4	71.2	1.0	58	1.0	16.0	93
+SMCJ60	GGH	GGH	66.7	81.5	1.0	60	1.0	14.0	107
+SMCJ60A	GGK	GGK	66.7	73.7	1.0	60	1.0	15.5	96
+SMCJ64	GGL	GGL	71.1	86.9	1.0	64	1.0	13.2	114
+SMCJ64A	GGM	GGM	71.1	78.6	1.0	64	1.0	14.6	103
+SMCJ70	GGN	GGN	77.8	95.1	1.0	70	1.0	12.0	125
+SMCJ70A	GGP	GGP	77.8	86.0	1.0	70	1.0	13.3	113
+SMCJ75	GGQ	GGQ	83.3	102	1.0	75	1.0	11.2	134
+SMCJ75A	GGR	GGR	83.3	92.1	1.0	75	1.0	12.4	121
+SMCJ78	GGs	GGs	86.7	106	1.0	78	1.0	10.8	139
+SMCJ78A	GGT	GGT	86.7	95.8	1.0	78	1.0	11.9	126
+SMCJ85	GGU	GGU	94.4	115	1.0	85	1.0	9.9	151
+SMCJ85A	GGV	GGV	94.4	104	1.0	85	1.0	10.9	137
+SMCJ90	GGW	GGW	100	122	1.0	90	1.0	9.4	160
+SMCJ90A	GGX	GGX	100	111	1.0	90	1.0	10.3	146
+SMCJ100	GGY	GGY	111	136	1.0	100	1.0	8.4	179
+SMCJ100A	GGZ	GGZ	111	123	1.0	100	1.0	9.3	162
+SMCJ110	GHD	GHD	122	149	1.0	110	1.0	7.7	196
+SMCJ110A	GHE	GHE	122	135	1.0	110	1.0	8.5	177
+SMCJ120	GHF	GHF	133	163	1.0	120	1.0	7.0	214
+SMCJ120A	GHG	GHG	133	147	1.0	120	1.0	7.8	193
+SMCJ130	GHH	GHH	144	176	1.0	130	1.0	6.5	231
+SMCJ130A	GHK	GHK	144	159	1.0	130	1.0	7.2	209
+SMCJ150	GHL	GHL	167	204	1.0	150	1.0	5.6	268
+SMCJ150A	GHM	GHM	167	185	1.0	150	1.0	6.2	243
+SMCJ160	GHN	GHN	178	218	1.0	160	1.0	5.2	287
+SMCJ160A	GHP	GHP	178	197	1.0	160	1.0	5.8	259
+SMCJ170	GHQ	GHQ	189	231	1.0	170	1.0	4.9	304
+SMCJ170A	GHR	GHR	189	209	1.0	170	1.0	5.5	275
SMCJ188	GHT	GHT	209	255	1.0	188	1.0	4.4	344
SMCJ188A	GHS	GHS	209	231	1.0	188	1.0	4.6	328

Notes: (1) Pulse test: $t_p \leq 50ms$

(2) Surge current waveform per Fig. 3 and derate per Fig. 2

(3) For bi-directional types having V_{WM} of 10 Volts and less, the I_D limit is doubled

(4) All terms and symbols are consistent with ANSI/IEEE C62.35

+ Underwriters Laboratory Recognition for the classification of protectors (QVGG2) under the UL standard for safety 497B and file number E136766 for both uni-directional and bi-directional devices

Ratings and Characteristic Curves ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig. 1 – Peak Pulse Power Rating Curve




Fig. 2 – Pulse Derating Curve




Fig. 3 – Pulse Waveform




Fig. 4 – Typical Junction Capacitance Uni-Directional




Fig. 5 – Typical Transient Thermal Impedance





Fig. 6 - Maximum Non-Repetitive Forward Surge Current Uni-Directional Use Only





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.