






REV.	DESCRIPTION	DATE
A	RELEASE	2012.11.12

NOTES:
 Insulator Material: Nylon-6T, UL 94V-0
 Contact Plating: Flash Gold
 Contact Material: Brass

Current Rating : 1A AC,DC
 Contact Resistance: 20MΩ Max.
 Dielectric Withstanding: AC 500V
 Insulator Resistance: 1000MΩ Min.
 Operating Temp.: -40°C~+105°C



NUMBER OF POSITIONS	DIMENSION		
	A	B	C
10	5.08	11.25	12.65
14	7.62	13.79	15.19
16	8.89	15.06	16.46
20	11.43	17.60	19.00
26	15.24	21.41	22.81
30	17.78	23.95	25.35
34	20.32	26.49	27.89
40	24.13	30.30	31.70
50	30.48	36.65	38.05
60	36.83	43.00	44.40

UNLESS TOLERANCE	
GENERAL	ANGLE
X: ± 0.30	X°: ± 3.0°
.X: ± 0.25	.X°: ± 2.0°
.XX: ± 0.20	.XX°: ± 1.0°
.XXX: ± 0.10	.XXX°: ± 0.5°

SCALE	SHEET	UNIT
1:1	1/1	MM

Port NO.:
3220-XX-0300-00
 CNC Tech, LLC
 DRAW NO.:
 REV: A