

RF AMPLIFIER

MODEL *TM7487*

Available as: TM7487, 4 Pin TO-8 (T4)
 TN7487, 4 Pin Surface Mount (SM3)
 FP7487, 4 Pin Flatpack (FP4)
 BX7487, Connectorized Housing (H1)

Features

- Low Noise Figure: 3 dB Typical
- Low Power Dissipation: 65 mW @ +5 Volts
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	5-350 MHz	10-300 MHz
Gain (dB)	15.5	14.5 Min.
Power @ 1 dB Comp. (dBm)	+8	+7.0 Min.
Reverse Isolation (dB)	-20	-19 Max.
VSWR In	<1.5:1	2.0:1 Max.
VSWR Out	<1.5:1	2.0:1 Max.
Noise Figure (dB)	3	4.0 Max.
Power Vdc	+5	+5 Min.
mA	13	14.5 Max.

Note: Care should always be taken to effectively ground the case of each unit.


Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point..... +36 dBm (Typ.)
 Second Order Two Tone Intercept Point..... +30 dBm (Typ.)
 Third Order Two Tone Intercept Point..... +22 dBm (Typ.)

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 8 Volts
 Continuous RF Input Power + 13 dBm
 Short Term RF Input Power 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.5 Watt (3 µsec Max.)

Typical Performance Data



Legend ——— + 25 °C - - - - + 85 °C ······ -55 °C

Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
5	.19	-72	5.47	-163	.08	18	.27	144
10	.10	-86	5.76	-173	.09	9	.18	142
50	.02	173	6.00	164	.09	-8	.09	-174
100	.04	100	5.99	145	.09	-19	.12	-153
150	.04	61	5.95	127	.10	-30	.15	-156
200	.02	26	5.96	108	.10	-40	.15	-168
250	.03	-136	6.00	89	.10	-53	.10	170
300	.11	-167	6.04	67	.10	-67	.04	58
350	.23	165	5.97	42	.10	-86	.21	-13



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

7/6/04

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001