


GD491SD**SURFACE MOUNT, SCHOTTKY BARRIER DIODE
VOLTAGE 25V, CURRENT 1A****Description**

The GD491SD is low power rectification for switching power supply.

Package Dimensions**Absolute Maximum Ratings at Ta = 25°C**

Parameter	Symbol	Ratings	Unit
Operating Junction Temperature	T _j	-50 ~ +125	°C
Storage Temperature	T _{stg}	-50 ~ +150	°C
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	25	V
Maximum RMS Voltage	V _{RPS}	18	V
Maximum DC Blocking Voltage	V _{DC}	20	V
Maximum Average Forward Rectified Current	I _o	1	A
Peak Forward Surge Current at 8.3mSec single half sine-wave	I _{FSM}	3.0	A
Typical Junction Capacitance between Terminal (Note 1)	C _J	30	pF
Total Power Dissipation	PD	225	mW






Electrical Characteristics (at TA = 25°C unless otherwise noted)

Parameter	Symbol	Min.	Max.	Unit	Test Conditions
Reverse Breakdown Voltage	V _{(BR)R}	25	-	V	I _R =100μA
Maximum Instantaneous Forward Voltage	V _F	-	450	mV	I _F =1A
Reverse Leakage Current	I _R	-	200	μA	V _R =20V

Notes: 1. Measured at 1.0 MHz and applied reverse voltage of 10 volts.

2. ESD sensitive product handling required.

Characteristics Curve



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- Taiwan: No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- China: (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165