



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: x.x=±0.4mm  
x.xx=±0.25mm
3. RATING: DC 30V, 0.3A
4. OPERATING FORCE: 200 ± 100gf
5. TRAVEL: 3.3mm FULL TRAVEL (B)
6. LIFE CYCLES: 10,000 CYCLES
7. OPERATING TEMPERATURE: -20°C TO 70°C
8. CONTACT RESISTANCE: 20 Milli-ohms MAX.
9. INSULATION RESISTANCE: 100 Mega-OHMS MIN@ 500VDC.
- ▲ 10. LED COLOR: BLUE
11. ▲ DENOTES CRITICAL PARAMETER.
12. 2002/95/EC (RoHS) COMPLIANT.

LED SPECS	UNITS	BLUE
FORWARD CURRENT	mA	20
FORWARD VOLTAGE @20mA	V	3.5 Typ - 4.0 Max
LUMINOUS INTENSITY @ 10mA	MCD	350



TITLE WBL2UOABQ				
SCALE 2	DATE 12/22/2010	DR BMA	DWG B400007	REV A

A	19543	Release For Production	12/22/10	BMA
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED