



5.0Amp. Surface Mount Schottky Barrier Diodes

SK520SC thru SK5100SC

Features

- For surface mounted applications.
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Plastic material used carries Underwriters Laboratory Flammability Classification 94V-0
- Low leakage current
- High surge capability
- High temperature soldering: 250°C/10 seconds at terminals
- Exceeds environmental standards of MIL-S-19500/228

Mechanical Data

- Case: Molded plastic, SMC/JEDEC DO-214AB.
- Terminals: Solder plated, solderable per MIL-STD-750 method 2026
- Polarity: Indicated by cathode band.
- Mounting Position : Any.
- Weight: 0.195 gram, 0.00585 ounce


Maximum Ratings and Electrical Characteristics

(Rating at 25°C ambient temperature unless otherwise specified.)


| Parameter | Symbol | Type | | | | | | | Units |
|---|--------------------|------------|-------|-------|------------|-------|-------|--------|----------|
| | | SK520 | SK530 | SK540 | SK550 | SK560 | SK580 | SK5100 | |
| Repetitive peak reverse voltage | V _{RRM} | 20 | 30 | 40 | 50 | 60 | 80 | 100 | V |
| Maximum RMS voltage | V _{RMS} | 14 | 21 | 28 | 35 | 42 | 56 | 70 | V |
| Maximum DC blocking voltage | V _R | 20 | 30 | 40 | 50 | 60 | 80 | 100 | V |
| Maximum instantaneous forward voltage, I _F =5A (Note 1) | V _F | 0.55 | 0.55 | 0.55 | 0.7 | 0.7 | 0.85 | 0.85 | V |
| Average forward rectified current | I _O | 5 | | | | | | | A |
| Peak forward surge current @8.3ms single half sine wave superimposed on rated load (JEDEC method) | I _{FSM} | 150 | | | | | | | A |
| Maximum DC reverse current V _R =V _{RRM} , T _A =25°C V _R =V _{RRM} , T _A =125°C | I _R | 0.5 50 | | | | | | | mA mA |
| Maximum thermal resistance, Junction to ambient | R _{th,JA} | 46(typ) | | | | | | | °C/W |
| Maximum thermal resistance, Junction to case | R _{th,JC} | 24(typ) | | | | | | | °C/W |
| Diode junction capacitance @ f=1MHz and applied 4VDC reverse voltage | C _J | 380(typ) | | | | | | | pF |
| Storage temperature | T _{stg} | -55 ~ +150 | | | | | | | °C |
| Operating temperature | T _J | -55 ~ +125 | | | -55 ~ +150 | | | | °C |

Characteristic Curves


Forward Current Derating Curve




Maximum Non-Repetitive Forward Surge Current




Forward Current vs Forward Voltage



Junction Capacitance vs Reverse Voltage



Reverse Leakage Current vs Reverse Voltage






Ordering Information

| Device | Package | Shipping | Marking |
|----------|---------|------------------------|---------|
| SK520SC | SMC | 3000 pcs / Tape & Reel | SS52 |
| SK530SC | SMC | 3000 pcs / Tape & Reel | SS53 |
| SK540SC | SMC | 3000 pcs / Tape & Reel | SS54 |
| SK550SC | SMC | 3000 pcs / Tape & Reel | SS55 |
| SK560SC | SMC | 3000 pcs / Tape & Reel | SS56 |
| SK580SC | SMC | 3000 pcs / Tape & Reel | SS58 |
| SK5100SC | SMC | 3000 pcs / Tape & Reel | S510 |


Recommended temperature profile for IR reflow



| Profile feature | Sn-Pb eutectic Assembly | Pb-free Assembly |
|--|-------------------------|------------------|
| Average ramp-up rate (Tsmax to Tp) | 3°C/second max. | 3°C/second max. |
| Preheat | | |
| -Temperature Min(Ts min) | 100°C | 150°C |
| -Temperature Max(Ts max) | 150°C | 200°C |
| -Time(ts min to ts max) | 60-120 seconds | 60-180 seconds |
| Time maintained above: | | |
| -Temperature (TL) | 183°C | 217°C |
| - Time (tL) | 60-150 seconds | 60-150 seconds |
| Peak Temperature(TP) | 240 +0/-5 °C | 260 +0/-5 °C |
| Time within 5°C of actual peak temperature(tp) | 10-30 seconds | 20-40 seconds |
| Ramp down rate | 6°C/second max. | 6°C/second max. |
| Time 25 °C to peak temperature | 6 minutes max. | 8 minutes max. |

Note : All temperatures refer to topside of the package, measured on the package body surface.

DO-214AB/SMC Dimension



DO-214AB/SMC Plastic
 Surface Mounted Package
 CYStek Package Code : SC

*:Typical

| DIM | Inches | | Millimeters | | DIM | Inches | | Millimeters | |
|-----|--------|-------|-------------|------|-----|--------|-------|-------------|------|
| | Min. | Max. | Min. | Max. | | Min. | Max. | Min. | Max. |
| A | 0.114 | 0.126 | 2.90 | 3.20 | E | 0.006 | 0.012 | 0.15 | 0.31 |
| B | 0.220 | 0.245 | 5.59 | 6.22 | F | 0.004 | 0.008 | 0.10 | 0.20 |
| C | 0.260 | 0.280 | 6.60 | 7.11 | G | 0.030 | 0.060 | 0.76 | 1.52 |
| D | 0.078 | 0.103 | 1.98 | 2.62 | H | 0.305 | 0.320 | 7.75 | 8.13 |

Notes : 1.Controlling dimension : millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material :

- Lead : Pure tin plated.
- Mold Compound : Epoxy resin family, flammability solid burning class:UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.