

## LC Male to LC Female Right Angle Adapter



## **TECHNICAL DATA SHEET**

**PE9398** 

## LC Male to LC Female Right Angle Adapter

### Configuration

Connector 1 LC Male
Impedance 1 50 Ohms
Connector 2 LC Female
Impedance 2 50 Ohms
Adapter Design Standard
Body Style Right Angle

## **Mechanical Specifications**

#### Size

 Length, in [mm]
 2.785 [70.74]

 Width/Dia., in [mm]
 1.5 [38.1]

 Height, in [mm]
 2.6 [66.04]

#### **Connector 1**

Type LC Male
Inner Conductor Material and Plating Silver
Coupling Nut Material and Plating Brass, Nickel
Hex Size, in. 11/2
Torque, in-lbs [Nm] 21 [2.37]
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

#### Connector 2

Type LC Female
Inner Conductor Material and Plating Silver
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

## Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

## **Plotted and Other Data**

Notes: Values at 25 °C, sea level

 $URL: \ http://www.pasternack.com/lc-male-lc-female-right-angle-adapter-pe9398-p.aspx$ 

LC Male to LC Female Right Angle Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# PE9398 CAD Drawing

LC Male to LC Female Right Angle Adapter

