


# UF800 thru UF8010

SURFACE MOUNT REVERSE VOLTAGE 50 TO 1000VOLTS

ULTRA FAST RECTIFIERS FORWARD CURRENT - 8.0 AMPERES



TO-220AC



## FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O Utilizing Flame Retardant Epoxy Molding Compound
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency
- Low forward voltage, high current capability
- High surge capacity
- Ultra Fast recovery times, high voltage
- High temperature soldering : 260°C / 10 seconds at terminals
- Pb free product available : 99% Sn above meet RoHS environment substance directive request

## MECHANICAL DATA

- Case: TO-220AC moldedplastic
- Terminals: Lead solderable per MIL-STD-202, Method 208
- Polarity: As marked
- Mounting Position: Any
- Weight: 0.08 ounce, 2.24 gram

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS @T<sub>A</sub>=25°C unless otherwise specified

Ratings at 25 °C J ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%

	UF800	UF801	UF802	UF803	UF804	UF806	UF808	UF8010	UNITS
Maximum Recurrent Peak Reverse Voltage	50	100	200	300	400	600	800	1000	V
Maximum Input RM S. Voltage	35	70	140	210	280	420	560	700	V
Maximum DC Blocking Voltage	50	100	200	300	400	600	800	1000	V
Maximum Average Forward Rectified Current at T <sub>c</sub> =100°C									A
Peak Forward Surge Current, 8.3 ms single half sine wave superimposed on rated load (JEDEC method)									A
Maximum Instantaneous Forward Voltage at 8.0 A per element				1.0		1.3	1.5	1.7	V
Maximum DC Reverse Current (Note 1) Ta=25°C at Rated DC Blocking Voltage Ta=125°C					10				A
Typical Junction Capacitance (Note 1)				80		50			pF
Maximum Reverse Recovery Time (Note 2)				50		75			nS
Typical Thermal Resistance Note R <sub>θJC</sub>				15					°CW
Operating and Storage Temperature Range T <sub>J</sub>				-55 to +150					°C

### NOTES:

1. Reverse Recovery Test Conditions: IF=0.5A, IR=1A, Irr=0.25A
2. Measured at 1 MHz and applied reverse voltage of 4.0 VDC
3. Thermal resistance from junction to ambient and from junction to lead length 0.375"(9.5mm) P.C.B. mounted

# UF800 thru UF8010

## SURFACE MOUNT REVERSE VOLTAGE 50 TO 1000VOLTS





Fig.1-REVERSERECOVERY TIME CHARACTERISTIC AND TEST CIRCUITDIAGRAM




Fig.2- FORWARD CHARACTERISTICS




Fig.3-FORWARD CURRENTDERATING CURVE




Fig.4-PEAK FORWARD SURGECURRENT




Fig.5- TYPICAL REVERSE CHARACTERISTICS




Fig.6-TYPICAL JUNCTION CAPACITANCE