

## F-96U

### Electrical Specifications (@25C)

1. Maximum Power: 60.0 VA
2. Primary: 115V 50/60 Hz
3. Secondary: 10.0VCT @ 6.0 Amps
4. Voltage Regulation: 15 % TYP @ full load to no load
5. Temperature Rise: 35C TYP (45C MAX allowed)

### Description:

The F-96U is part of a series which has a long history of reliable service in the field, made from a proven design and constructed with UL recognized materials.

### Construction:

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

### Safety:

These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings as well as between the primary / secondary windings and the core.


### Dimensions: Units: In inches

A	B	C	D	E	F
3.00	2.50	2.750	2.00	2.312	1.312

Lead length: 7.0 inches  $\pm$  1 inch

Weight: 2.10 lbs



### Schematic:



Primary: Black to Black  
Secondary: Green to Green

**RoHS Compliance:** As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

\* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.



MTG-SLOTS 3/16 X 3/8" 4 SLOTS.

