

eATVS-4 & eATVS-8TM

AUTOMATIC TEMPERATURE AND VELOCITY SCANNER

The eATVS-4™ and eATVS-8™ Automatic Temperature and Velocity Scanners are portable, 4- and 8-channel hot wire anemometer systems. Fully automated, these research-quality instruments take accurate single- or multi-point measurements of air temperature, velocity and surface temperature in complex environments, such as PCBs and electronics enclosures. When used as temperature loggers, they can measure both fluid and solid temperatures.



Usable in rackmount or desktop configurations, eATVS-4™ and eATVS-8™ employ patented, fast response, omni-directional sensors, which measure both temperature and velocity. This patented single-sensor technology eliminates errors introduced as a result of air flow being nonisothermal. Each precisely calibrated sensor is flexible and robust with a low-profile configuration that allows OVERALL DIMENSIONS (D X W X H)

minimally intrusive mounting throughout the peaks and valleys created by the PCB components. These systems require a PC to operate and utilize the stageVIEW™ software for data acquisition and reporting.

stage $VIEW^{TM}$ software for automated data acquisition and reduction

235 mm x 134 mm x 64 mm (9.25" x 5.25" x 2.5")

TEMPERATURE RANGE

-20 °C to 120 °C ± 1 °C

FLOW RANGE

0 to 51 m/s (0 to 10,000 ft/min) (± 2%)

NUMBER OF CHANNELS

eATVS-4: Up to 4 eATVS-8: Up to 8

SOFTWARE

stageVIEW™

POWER

110V or 220V

WEIGHT

2 kg (4 lbs.)

CONNECTION

USB port

For further technical information, please contact Advanced Thermal Solutions, Inc. at 1-781-769-2800 or www.qats.com

FEATURES:

Single Sensor Technology

The only system that can measure both temperature and air velocity with a single sensor

» Accuracy and Ease of Use

Offers research quality results with the ease of use of handheld meter

>> Up to 8 Sensors

For simultaneous single point measurement of air velocity & temperature

» Connection

Requires a PC to operate and is compatible via USB port

» High & Low Speed Calibration

Sensors are calibrated for both low (natural convection) and high velocity flows from 0 to 51 m/s (10,000 ft/min)

» stageVIEW™ Software

For automated data acquisition, reporting and special thermal analysis module for quick evaluation of component temperature

Sensor Ports

Measure velocity and temperature through the ports holes

>> Free Lifetime Tech Support

