



SPECIFICATIONS

FREQUENCY RANGE: DC - 3 GHz
 INSERTION LOSS: .5 dB
 IMPEDANCE: 50 OHMS
 DC BLOCKING: NONE. WILL PASS DC FOR POWER AND CONTROL PURPOSES.
 MAX DC OR PEAK AC IS 150V
 FIRING POINT: 350V \pm 15% @ <100V/S>1000@5kv/ μ sRISE
 BREAKDOWN VOLTAGE: 20 TO 30V
 SURGE CURRENT: 5000A (8/20 μ s PLUS)
 PLUG LIFE: >600 TIMES @ 500A PLUSE(FIELD REPLACEABLE)
 POWER HANDLING: 2000 WATTS



PASTERNAK ENTERPRISES, INC.
 P.O BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451
 WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS

DWG TITLE		DES.			
PE7301-4		N FEMALE BULKHEAD, COAX SURGE PROTECTOR			
REV. A	FSCM NO. 53919	CAD FILE 051109	SCALE N/A	SIZE A	127

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES.