

S100-28


FEATURES:

- $P_G = 16$ dB min. at 100 W/30 MHz
- High linear power output
- **IMD** = -32 dBc max. at 100 W(PEP)
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	20 A
V_{CES}	70 V
V_{CEO}	33 V
V_{EBO}	4.0 V
P_{DISS}	250 W @ $T_C = 25^\circ C$
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	0.7 °C/W


PACKAGE STYLE .500 4L FLG



DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	220 / 5.59	230 / 5.84
B		.125 / 3.18
C	245 / 6.22	255 / 6.48
D	720 / 18.28	7.30 / 18.54
E		.125 / 3.18
F	970 / 24.64	980 / 24.89
G	495 / 12.57	505 / 12.83
H	.003 / 0.08	.007 / 0.18
I	.090 / 2.29	.110 / 2.79
J	.150 / 3.81	.175 / 4.45
K		.280 / 7.11
L	980 / 24.89	1.050 / 26.67

CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	$I_C = 50$ mA	33			V
BV_{CES}	$I_C = 100$ mA	70			V
BV_{EBO}	$I_E = 5.0$ mA	4.0			V
I_{CES}	$V_{CE} = 28$ V			30	mA
h_{FE}	$V_{CE} = 5.0$ V $I_C = 10$ A	10		100	---
C_{ob}	$V_{CB} = 28$ V $f = 1.0$ MHz	---	270	---	pF
G_p	$V_{CE} = 28$ V $P_{IN} = 2.5$ W $f = 30$ MHz	16			dB
η_c		65			%
VSWR				$\infty:1$	---
IMD	$P_{OUT} = 100$ W (PEP)			-32	dBc



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

Quality Semi-Conductors