


**Silicon PNP Power Transistor**

**DESCRIPTION**

- High Collector Current:  $I_C = -7A$
- Low Collector Saturation Voltage  
 :  $V_{CE(sat)} = -0.5V(Max) @ I_C = -4A$
- Complement to Type 2SD1237


**APPLICATIONS**

- Designed for large current switching applications.




**ABSOLUTE MAXIMUM RATINGS ( $T_a = 25^\circ C$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	-120	V
$V_{CEO}$	Collector-Emitter Voltage	-80	V
$V_{EBO}$	Emitter-Base Voltage	-6	V
$I_C$	Collector Current-Continuous	-7	A
$I_{CM}$	Collector Current-Peak	-12	A
$P_C$	Total Power Dissipation @ $T_c = 25^\circ C$	40	W
	Total Power Dissipation @ $T_a = 25^\circ C$	1.75	
$T_J$	Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature Range	-55~150	$^\circ C$



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.



# Silicon PNP Power Transistor

# 2SB921

## ELECTRICAL CHARACTERISTICS

$T_c=25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	$I_C = -1\text{mA}; R_{BE} = \infty$	-80			V
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	$I_C = -1\text{mA}; I_E = 0$	-120			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	$I_E = -1\text{mA}; I_C = 0$	-6			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = -4\text{A}; I_B = -0.4\text{A}$			-0.5	V
$I_{CBO}$	Collector Cutoff Current	$V_{CB} = -80\text{V}; I_E = 0$			-0.1	mA
$I_{EBO}$	Emitter Cutoff Current	$V_{EB} = -4\text{V}; I_C = 0$			-0.1	mA
$h_{FE-1}$	DC Current Gain	$I_C = -1\text{A}; V_{CE} = -2\text{V}$	70		280	
$h_{FE-2}$	DC Current Gain	$I_C = -4\text{A}; V_{CE} = -2\text{V}$	30			
$f_T$	Current-Gain—Bandwidth Product	$I_C = -1\text{A}; V_{CE} = -5\text{V}$		20		MHz

### ◆ $h_{FE-1}$ Classifications

Q	R	S
70-140	100-200	140-280